Wiring Device-Kellems

# Signal and Control Products, Mini-Quick, Female Plug, 5-Pole, Field Attachable, F9



By Hubbell Wiring Device-Kellems
Catalog # HCMS05F9

Signal and Control Products, Mini-Quick, Female Plug, 5-Pole, Field Attachable, F9

## Features

- Superior Contact Design
- Body with High Impact Design
- Precision Wire Funnels Eliminate Stray Strands

## Application

Quick Connect/Disconnect Signal and Control

## General

| | |
|---|---|
| EU RoHS Indicator | No |
| Environmental Conditions | IP67 Ingress Protection |
| Item Type | Female Straight Plug |
| Material - Coupling Nut | Aluminum |
| Material - Insert | PUR/PA |
| Material - O-Ring | Neoprene |
| Material - Overmold | PBT |
| Material - Shell | PBT |
| OEM Brand Name | Hubbell Wiring Device-Kellems |
| Operating Temperature | -40 Deg C to 85 Deg C |
| Performance | • Electrical - Amperage - 3 Pin - 12A<br>• 4,5 Pin - 9A<br>• Electrical - Maximum Wire Size - #16 AWG<br>• Electrical - Voltage Rating - 250V<br>• Environmental - Moisture Resistance - IP66 Suitability<br>• Environmental - Operating Temperature - -40°C to 85°C |
| Thread Size | Non-Threaded |
| UPC | 783585192215 |

## Electrical Ratings

| | |
|---|---|
| Amperage Rating | 9 A |
| Current / Amperage Rating | 9 A |
| Current Rating | 9 A |
| Voltage Rating | 250V kV |

## Conductor Related

| | |
|---|---|
| Cable Size | .24"-.32" |
| Cable Specification | UL Listed Portable Cord |

## Certifications and Compliance

| | |
|---|---|
| Industry Standard(s) | • CSA Certified, C22.2 No. 182.3 and CSA C22.2 No. 94.2-07<br>• UL 2238 and UL50E, File No. E192071 |

## Logistics

| | |
|---|---|
| Carton Quantity | 30 |

## Product Assets

Literature - WIRING_WLFVM034
Literature - Pulp & Paper Solutions
Sales Drawings - WDK_HCMS_DRAWING_PDF
Warranty - Industrial & Commercial Products



©2023 Hubbell Incorporated. All rights reserved.