Wiring Device-Kellems

Signal and Control, Micro Quick, Female Plug, Field Attachable, 4-Pole, .24-.35" Cable Range



By Hubbell Wiring Device-Kellems
Catalog # MCMS14F9

Signal and Control, Micro Quick, Female Plug, Field Attachable, 4-Pole, .24-.35" Cable Range

Features

- Body with high impact design
- Strain relief protects terminations
- Precision wire funnels eliminate stray strands

Application

Quick Connect/Disconnect Signal and Control

General

EU RoHS Indicator	No
Environmental Conditions	IP67 Ingress Protection
Item Type	Female Straight Plug
Material - Coupling Nut	Aluminum
Material - Insert	PUR/PA
Material - O-Ring	Neoprene
Material - Overmold	PBT
Material - Shell	PBT
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	-40 Deg C to 85 Deg C
Performance	• Electrical - Amperage - 4A • Electrical - Maximum Wire Size - #18 AWG • Electrical - Voltage Rating - 250V • Environmental - Moisture Resistance - IP66 Suitability • Environmental - Operating Temperature - -40°C to 90°C
Thread Size	Non-Threaded
UPC	783585192420

Electrical Ratings

Amperage Rating	4 A
Current / Amperage Rating	4 A
Current Rating	4 A
Voltage Rating	250V kV

Conductor Related

Cable Size	.24"-.32"
Cable Specification	UL Listed Portable Cord

Certifications and Compliance

Industry Standard(s)	• CSA Certified, C22.2 No. 182.3 and CSA C22.2 No. 94.2-07 • UL 2238 and UL50E, File No. E192071

Logistics

Carton Quantity	30

Product Assets

Literature - WIRING_WLFVM034
Literature - Pulp & Paper Solutions
Sales Drawings - WDK_MCMS14F9_DRAWING_PDF
Warranty - Industrial & Commercial Products

©2023 Hubbell Incorporated. All rights reserved.