# King Crimp™ Style Ferrules

**Only use the crimp style shanks with the crimp style sleeves and ferrules.** Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon™ products.



| Hose ID | Hose OD | | *Carbon Steel* | | *304 Stainless Steel* | | Work. Pressure (PSI) | | Ferrule ID | Ferrule Wall Thickness | Ferrule Overall Length |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | From | To | Part # | Price | Part # | Price | cam & groove[1] | KC nipple[2] | | | |
| 3" | 3-13/64" | 3-16/64" | ***CF300-1CS*** | **$17.50** | ***CF300-1SS*** | **$28.95** | 150 | 300 | 3.313" | .090" | 4" |
| | 3-17/64" | 3-20/64" | ***CF300-2CS*** | **17.50** | ***CF300-2SS*** | **28.95** | 150 | 300 | 3.375" | .090" | 4" |
| | 3-21/64" | 3-24/64" | ***CF300-3CS*** | **17.50** | ***CF300-3SS*** | **28.95** | 150 | 300 | 3.438" | .090" | 4" |
| | 3-25/64" | 3-28/64" | ***CF300-4CS*** | **17.50** | ***CF300-4SS*** | **28.95** | 150 | 300 | 3.500" | .090" | 4" |
| | 3-29/64" | 3-32/64" | ***CF300-5CS*** | **17.50** | ***CF300-5SS*** | **28.95** | 150 | 300 | 3.563" | .090" | 4" |
| | 3-33/64" | 3-36/64" | ***CF300-6CS*** | **17.50** | ***CF300-6SS*** | **28.95** | 150 | 300 | 3.625" | .090" | 4" |
| | 3-37/64" | 3-40/64" | ***CF300-7CS*** | **17.50** | ***CF300-7SS*** | **28.95** | 150 | 300 | 3.688" | .090" | 4" |
| | 3-41/64" | 3-44/64" | ***CF300-8CS*** | **17.50** | ***CF300-8SS*** | **28.95** | 150 | 300 | 3.750" | .090" | 4" |
| | 3-45/64" | 3-48/64" | ***CF300-9CS*** | **17.50** | ***CF300-9SS*** | **28.95** | 150 | 300 | 3.813" | .090" | 4" |
| | 3-49/64" | 3-52/64" | ***CF300-10CS*** | **17.50** | ***CF300-10SS*** | **28.95** | 150 | 300 | 3.875" | .090" | 4" |
| | 3-53/64" | 3-56/64" | ***CF300-11CS*** | **17.50** | ***CF300-11SS*** | **28.95** | 150 | 300 | 3.938" | .090" | 4" |
| | 3-57/64" | 3-60/64" | ***CF300-12CS*** | **17.50** | ***CF300-12SS*** | **28.95** | 150 | 300 | 4.000" | .090" | 4" |
| | 3-61/64" | 4" | ***CF300-13CS*** | **17.50** | ***CF300-13SS*** | **28.95** | 150 | 300 | 4.063" | .090" | 4" |
| | 4-1/64" | 4-4/64" | ***CF300-14CS*** | **17.50** | ***CF300-14SS*** | **28.95** | 150 | 300 | 4.125" | .090" | 4" |
| | 4-5/64" | 4-8/64" | ***CF300-15CS*** | **17.50** | ***CF300-15SS*** | **28.95** | 150 | 300 | 4.188" | .090" | 4" |
| | 4-9/64" | 4-12/64" | ***CF300-16CS*** | **17.50** | ***CF300-16SS*** | **28.95** | 150 | 300 | 4.250" | .090" | 4" |
| 4" | 4-13/64" | 4-16/64" | ***CF400-1CS*** | **23.00** | ***CF400-1SS*** | **67.20** | 150 | 300 | 4.313" | .090" | 4" |
| | 4-17/64" | 4-20/64" | ***CF400-2CS*** | **23.00** | ***CF400-2SS*** | **67.20** | 150 | 300 | 4.375" | .090" | 4" |
| | 4-21/64" | 4-24/64" | ***CF400-3CS*** | **23.00** | ***CF400-3SS*** | **67.20** | 150 | 300 | 4.438" | .090" | 4" |
| | 4-25/64" | 4-28/64" | ***CF400-4CS*** | **23.00** | ***CF400-4SS*** | **67.20** | 150 | 300 | 4.500" | .090" | 4" |
| | 4-29/64" | 4-32/64" | ***CF400-5CS*** | **23.00** | ***CF400-5SS*** | **67.20** | 150 | 300 | 4.563" | .090" | 4" |
| | 4-33/64" | 4-36/64" | ***CF400-6CS*** | **23.00** | ***CF400-6SS*** | **67.20** | 150 | 300 | 4.625" | .090" | 4" |
| | 4-37/64" | 4-40/64" | ***CF400-7CS*** | **23.00** | ***CF400-7SS*** | **67.20** | 150 | 300 | 4.688" | .090" | 4" |
| | 4-41/64" | 4-44/64" | ***CF400-8CS*** | **23.00** | ***CF400-8SS*** | **67.20** | 150 | 300 | 4.750" | .090" | 4" |
| | 4-45/64" | 4-48/64" | ***CF400-9CS*** | **23.00** | ***CF400-9SS*** | **67.20** | 150 | 300 | 4.813" | .090" | 4" |
| | 4-49/64" | 4-52/64" | ***CF400-10CS*** | **23.00** | ***CF400-10SS*** | **67.20** | 150 | 300 | 4.875" | .090" | 4" |
| | 4-53/64" | 4-56/64" | ***CF400-11CS*** | **23.00** | ***CF400-11SS*** | **67.20** | 150 | 300 | 4.938" | .090" | 4" |
| | 4-57/64" | 4-60/64" | ***CF400-12CS*** | **23.00** | ***CF400-12SS*** | **67.20** | 150 | 300 | 5.000" | .090" | 4" |
| | 4-61/64" | 5" | ***CF400-13CS*** | **23.00** | ***CF400-13SS*** | **67.20** | 150 | 300 | 5.063" | .090" | 4" |
| | 5-1/64" | 5-4/64" | ***CF400-14CS*** | **23.00** | ***CF400-14SS*** | **67.20** | 150 | 300 | 5.125" | .090" | 4" |
| | 5-5/64" | 5-8/64" | ***CF400-15CS*** | **23.00** | ***CF400-15SS*** | **67.20** | 150 | 300 | 5.188" | .090" | 4" |
| | 5-9/64" | 5-12/64" | ***CF400-16CS*** | **23.00** | ***CF400-16SS*** | **67.20** | 150 | 300 | 5.250" | .090" | 4" |
| 6" | 6-21/64" | 6-28/64" | ***CF600-1CS*** | **52.25** | ***CF600-1SS*** | **85.00** | * | * | 6.500" | .120" | 5-7/8" |
| | 6-29/64" | 6-36/64" | ***CF600-2CS*** | **52.25** | ***CF600-2SS*** | **85.00** | * | * | 6.625" | .120" | 5-7/8" |
| | 6-37/64" | 6-44/64" | ***CF600-3CS*** | **52.25** | ***CF600-3SS*** | **85.00** | * | * | 6.750" | .120" | 5-7/8" |
| | 6-45/64" | 6-52/64" | ***CF600-4CS*** | **52.25** | ***CF600-4SS*** | **85.00** | * | * | 6.875" | .120" | 5-7/8" |
| | 6-53/64" | 6-60/64" | ***CF600-5CS*** | **52.25** | ***CF600-5SS*** | **85.00** | * | * | 7.000" | .120" | 5-7/8" |
| | 6-61/64" | 7-4/64" | ***CF600-6CS*** | **52.25** | ***CF600-6SS*** | **85.00** | * | * | 7.125" | .120" | 5-7/8" |
| | 7-5/64" | 7-12/64" | ***CF600-7CS*** | **52.25** | ***CF600-7SS*** | **85.00** | * | * | 7.250" | .120" | 5-7/8" |
| | 7-13/64" | 7-20/64" | ***CF600-8CS*** | **52.25** | ***CF600-8SS*** | **85.00** | * | * | 7.375" | .120" | 5-7/8" |
| | 7-21/64" | 7-28/64" | ***CF600-9CS*** | **52.25** | ***CF600-9SS*** | **85.00** | * | * | 7.500" | .120" | 5-7/8" |

* consult Dixon™ for pressure rating
[1] based on using crimp cam and groove shanks
[2] based on using King™ combination nipples