Hammond Power Solutions

LR 3902

DRY TYPE TRANSFORMER 77U5 E112313 LISTED

GUELPH, ONT. BARABOO,WI COMPTON, CA MONTERREY, MX


THREE PHASE DRY TYPE DRIVE ISOLATION TRANSFORMER
TRANSFORMATEUR TRIPHASÉ POUR VARIATEUR DE VITESSE DE MOTEURS

HV/HT	230V
BIL	–
TERM. BORNES	H1 H2 H3

VOLTS	CURRENT COURANT	% RATED VOLTAGE % TENSION NOMINALE	CONNECTION EACH PHASE CONNEXION PAR PHASE
242	64.5	105	1
230	67.8	100	2
218	71.3	95	3

LV/BT	230Y/133V
BIL	–
TERM. BORNES	X0 X1 X2 X3

Cust. Ref. Réf. du client	
Serial No. No. de série	
Part No. No. de pièce	DM027CC
kVA	27
TYPE	K
Cooling Refroidissement	ANN
Temp. Rise Échauffement	150 ° C
Temp. Class Classe de Temp.	220 ° C
Frequency Fréquence	60 Hz
Impédance % @ 170 °C	5.4
Encl. Type Type de boîtier	3R
Wt Poids lbs/kg	285/130
Winding Enroulement	AL



SPACINGS BETWEEN ANY VENTILATED ENCLOSURE PANEL AND ANY ADJACENT WALL SHALL BE A MINIMUM OF 3 INCHES

d0031022b

8 03423 00289 3

TITLE:	3PH DRIVE TRANSFORMER NAMEPLATE INFORMATION			
5	21/07/13	PP	EDB UPDATE	DES: MBURSAC
4	14/10/22	RM	HCN: 50634	DATE: 01/01/29
NO.	DATE	BY	REVISION	SCALE: NTS


Hammond Power Solutions Inc.

SHEET 1 OF 2


EDBDM027CC

5.1 gcalota 2021/07/27 15:54

FRONT VIEW



SIDE VIEW



All Dimensions in inches[mm]

ENCLOSURE COLOR : ANSI 61 GREY – OUTDOOR

HV TERMINAL DETAIL

MECHANICAL TYPE LUGS INCLUDED
SUITABLE FOR #14–2 CU/AL
CONDUCTORS
1 CONDUCTOR PER PHASE

LV TERMINAL DETAIL

MECHANICAL TYPE LUGS INCLUDED
SUITABLE FOR #14–2 CU/AL
CONDUCTORS
1 CONDUCTOR PER PHASE

CUSTOMER NOTES:

– HV TERMINATED AT TOP FRONT
– LV TERMINATED AT BOTTOM FRONT
– C/W 1–"NC"– THERMOSTAT PER COIL CONNECTED TO T.B.

Hammond Power Solutions Inc.

TITLE: 3PH DRIVE TRANSFORMER

NO.	DATE	BY	REVISION	
5	21/07/13	PP	EDB UPDATE	DES: MBURSAC
4	14/10/22	RM	HCN: 50634	DATE: 01/01/29
				SCALE: NTS

SHEET 2 OF 2

EDBDM027CC

5.1 gcalota 2021/07/27 15:54