Bulkhead Fittings

Application:
- for use on most poly storage tanks and many steel and fiberglass tanks

Features:
- glass reinforced polypropylene provides strength and chemical resistance
- EPDM gaskets are standard
- FKM gaskets are available, contact Dixon® to order


63931


63481


63683

female NPT fittings

Female NPT	Hole Size	*Polypropylene* Part #
½"	1-7/16"	***62834***
¾"	1-7/16"	***60401***
1"	2-1/4"	***60427***
1¼"	2-1/4"	***60403***
1½"	3"	***60124*** NEW
1½"	2-3/8"	***63931*** [1]
2"	3"	***60405***
2"	3"	***63481*** [2]
2" HD [3]	3-1/4"	***63683***
3"	4-1/2"	***62299*** [1]

[1] 1½" and 3" do not contain a washer
[2] designed for tank wall thickness less than ⅜" - low profile

Gaskets

Size	*EPDM* Part #
½" - ¾"	***60402***
1" - 1¼"	***60404***
1½"	***63938***
2"	***60406***
2" HD [1]	***60336***
3"	***60331***



[1] heavy duty

Bulkhead Couplings

Female NPTF	External Male UNS	Length	*Brass* Part #
⅛"	5/8"	1.50"	***207BH2***
¼"	3/4"	1.50"	***207BH4***
¼"	3/4"	.94"	***207BH4S***
⅜"	1"	1.31"	***207BH6***
½"	1-1/8"	1.50"	***207BH8***
¾"	1-5/16"	1.50"	***207BH12***



Note: washer nut is 12L14 steel