Medium Voltage Transformer - Three Phase, 4160Δ - 480ΔV, 30kVA

By Acme Electric
Catalog # WI030K18



*Representative Image

Medium Voltage Transformer - Three Phase, 4160Δ - 480ΔV, 30kVA

Features

- Lower operating cost over Liquid-filled
- No additional fireproofing or venting
- Long life expectancy
- Smaller, lighter easy to maintain

General

Construction	Ventilated
Mounting Type	Floor
Primary Voltage	4160Δ
Product Category	Medium Voltage Transformer
Secondary Voltage	480D V
UPC	047503097779
Winding Material	AL
kVA	30

Dimensions

Depth	20.0 in
Height	38.5 in
Weight	485 lb
Width	28.5 in

Electrical Ratings

Efficiency	97.90%
Frequency Rating	60 Hz
Primary Voltage	4160D V

Certifications and Compliance

CSA Standard	C22.2 No. 47
Dept of Energy Regulation	Meets or exceed U.S. DOE 10 CFR Part 431
Nema Rating	NEMA 1
UL Standard	UL 1562

Product Assets

Brochures - MediumVoltageTransformers
Catalogs - Acme Electric Catalog - Section 2 - Medium Voltage Transformers
Customer Notices - Prop65_Cancer
Installation Manuals - General Purpose Dry-Type Distribution Transformer
SDS - HCC_SDS
Terms and Conditions - HCC Terms & Conditions

©2023 Hubbell Incorporated. All rights reserved.