WSREM



Handheld wireless configuration tool enables contractors and end-users to customize sensor control settings for PORTO fixtures with the simple click of a button - no ladders required.

Color: Bronze

Weight: 0.0 lbs

Project:	Type:
Prepared By:	Date:

Technical Specifications

Sensor Specifications

Power Consumption:
1W

0-10V Sinking Current:
50mA

Adjustable High and Low Modes:
High: 0-10V; Low: off, 0-9.8V

Adjustable Time Delay:
Amount of time in high mode with no motion before switching to low mode: 5 min., 1 -30 min.

Adjustable Cut Off Delay:
Time in which the fixture will remain on low mode with no motion before turning off and waiting for new motion to turn on: None, 1 -60 min., 1 -5 hrs.

Adjustable Sensitivy:
None, low, medium, maximum

Adjustable Setpoint:
None, 1 to 250 fc, auto

Operating Temperature:
-40°F to 167°F (-40°C to +75°C)

Operating Humidity:
20% to 90% noncondensing

Relay Life Rating:
200,000 cycles (120/277VAC), 50,000 cycles (230VAC)

IP Rating:
Ingress protection rating of IP66 for dust and water

UL Listed:
Suitable for Wet Locations as factory installed

Other

Compatible Products:
AEROBAY with /PIR
RAIL with /PIR
VANLED with /WS or /WS2
IVEPARK with /WS or /WS2
PORTO with /WS or /WS2
IVELOT with /WS, /WS2, or /WS4
ALED with /WS2, or /WS4

Buy American Act Compliance:
RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice