orbit
Orbit Industries, Inc.

5S Deep Boxes

4-11/16" SQUARE (5S) BOXES
WELDED
2-1/8" DEEP
42.0 Cu. In.

WITH RAISED GROUND EMBOSS (EXCEPT FOR BRACKETED BOXES AND EXTENSION RINGS)

Metal Stud Bracket Features:
- U.S. Patent No.: 8,262,043
- Metal Stud (MS) Bracket engages on either side of metal stud


***Model Revised Feb. 2008**


Boxes with Pigtail Features:
- 7" Solid Cu. #12AWG Pigtail Pre-assembled with Ground Emboss and 10-32 Ground Screw
- 10" Pigtail for BSA Series


BSA Features:
- See page A11


- 600V MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- Visit www.ul.com or QCIT Guide on page W1 for more information


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
5SDB-50	-	12 - 1/2"	4 - 1/2"	24
5SDB-50-FB	FB, Flush	9 - 1/2"	5 - 1/2"	24
5SDB-50/75	-	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	24
5SDB-50/75-FB	FB, Flush	6 - 1/2", 3 - 3/4"	3 - 1/2", 2 - 3/4"	24
5SDB-75	-	12 - 3/4"	2 - 1/2", 2 - 3/4"	24
5SDB-75-FB	FB, Flush	9 - 3/4"	3 - 1/2", 2 - 3/4"	24
5SDB-75/100	-	4 - 3/4" , 4 - 1"	2 - 1/2", 2 - 3/4"	24
5SDB-75/100-FB	FB, Flush	3 - 3/4" , 3 - 1"	3 - 1/2", 2 - 3/4"	24
5SDB-100	-	8 - 1"	2 - 1/2", 2 - 3/4"	24
5SDB-100-FB	FB, Flush	6 - 1"	3 - 1/2", 2 - 3/4"	24
5SDB-125	-	6 - 1-1/4"	2 - 1/2", 2 - 3/4"	24
5SDB-MKO	-	2 - 1/2", 10 - MKO	2 - 1/2", 2 - MKO	24
5SDB-MKO-PT	-	2 - 1/2", 10 - MKO	2 - 1/2", 2 - MKO	24
5SDB-MKO-FB	FB, Flush	2 - 1/2", 7 - MKO	3 - 1/2", 2 - MKO	24
5SDB-MKO-MS*	MS, Self-Gripping + Box Support Clip	2 - 1/2", 7 - MKO	3 - 1/2", 2 - MKO	24
5SDB-50/75-EXT	-	8 - 1/2", 4 - 3/4"	-	24
5SDB-MKO-EXT	-	2 - 1/2", 10 - MKO	-	24
5SDB-50/75-PT-BSA	Back Support Arm	8 - 1/2", 4 - 3/4"	3 - 3/4"	24
5SDB-50/75-AB-PT-BSA	AB, Flush, Back Support Arm	6 - 1/2", 3 - 3/4"	3 - 3/4"	24



5SDB-50



5SDB-50-FB



5SDB-50/75



5SDB-50/75-FB



5SDB-75



5SDB-75-FB



5SDB-75/100



5SDB-75/100-FB



5SDB-100



5SDB-100-FB



5SDB-125



5SDB-MKO



5SDB-MKO-PT



5SDB-MKO-FB


5SDB-MKO-MS*


5SDB-50/75-EXT


5SDB-MKO-EXT


5SDB-50/75-PT-BSA


5SDB-50/75-AB-PT-BSA

RoHS UL File E227970