4-11/16" SQUARE (5S) BOXES
DRAWN
2-1/8" DEEP
42.0 Cu. In.

WITH RAISED GROUND EMBOSS & 10-32 GROUND SCREW

EXTENSIVE CROSS REFERENCE AVAILABLE IN SECTION X

Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
D5SDB-50/75	-	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	24
D5SDB-50/75-FB	FB, Flush	6 - 1/2", 3 - 3/4"	2 - 1/2", 2 - 3/4"	24
D5SDB-CKO	-	2 - 1/2", 10 - CKO	2 - 1/2", 2 - 3/4"	24
D5SDB-CKO-FB	FB, Flush	2 - 1/2", 7 - CKO	2 - 1/2", 2 - 3/4"	24
D5SDB-CKO-S	-	2 - 1/2", 10 - CKO	3 - 3/4"	24


D5SDB-50/75


D5SDB-50/75-FB


D5SDB-CKO


D5SDB-CKO-FB


D5SDB-CKO-S

4-11/16" SQUARE (5S) SUPER SHALLOW BOX & EXTENSION RING
WELDED
1-1/2" DEEP
29.5 Cu. In.

WITH RAISED GROUND EMBOSS (EXCEPT FOR EXTENSION RING)

Cat. No.	Knockouts		Std. Pkg.
	Sides	Bottom	
5SSB-MKO	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	24
5SSB-MKO-EXT	8 - 1/2", 4 - MKO	-	24


5SSB-MKO


5SSB-MKO-EXT

4-11/16" SQUARE (5S) LARGE CAPACITY BOXES
WELDED
2-1/2" DEEP
49.4 Cu. In.

WITH RAISED GROUND EMBOSS & TWO #8-32 x 1/2" MOUNTING SCREWS

Features:
- Suitable for Datacom & Electrical Applications

ORBIT INDUSTRIES EXCLUSIVE

- **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- Visit www.ul.com or QCIT Guide on page W1 for more information

Cat. No.	Knockouts		Std. Pkg.
	Sides	Bottom	
5SLB-MKO	8 - 1/2", 4 - 1/2" & 3/4" M.K.O.	2 - 1/2", 2 - 3/4"	24
5SLB-2MKO	4 - 3/4" & 1" M.K.O., 4 - 1" & 1 - 1/4" M.K.O.	2 - 1/2", 2 - 3/4"	24


5SLB-MKO


5SLB-2MKO

File E227970 UL RoHS