ODP-2-26050-3H04B-MN

Optidrive P2 VFD Datasheet



5 HP, 6.5 A, 500-600 V, 3PH

IP66 Switched Outdoor Variable Frequency Drive with TFT Display

Input Ratings

Supply Voltage	500-600 V
Input Phases	3
Supply Current Continuous	7.8 A
Supply Fuse or MCB (Type B)	10 A

Output Ratings

Motor Output Rating	4 kW (5 HP)
Output Voltage	0 – Supply Voltage
Output Current	6.5 A

Cable Information

Max Supply Cable Size	8 mm² (0.01 sq in)
Max Motor Cable Size	8 mm² (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	No Internal EMC
Brake Transistor	Internal
Enclosure	IP66 Switched Outdoor
Display	TFT Display
PCB Coating	Standard

Dimensions

Size	2
Height	257 mm (10.12 in)
Width	188 mm (7.4 in)
Depth	172 mm (6.77 in)
Weight	3.5 kg (7.72 lbs)
Fixings	4 x M4


Packaged Dimensions

Height	215 mm (8.46 in)
Width	235 mm (9.25 in)
Depth	375 mm (14.76 in)
Weight	4.2 kg (9.26 lbs)


Buy this drive or get more information
Find your local sales partner on
invertekdrives.com

Invertek Drives.com

How we measure our drives and packaging



Drive Dimensions



Packaging Dimensions

Buy this drive or get more information
Find your local sales partner on
invertekdrives.com

Invertek Drives.com