HazMat 20-Gallon Overpack Salvage Drum Spill Kit #SPKHZ-20 - Absorbs up to 15.2 Gallons



Be prepared for fast response with a SpillTech® HazMat Overpack Salvage Drum Spill Kit!

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com

6455 East Johns Crossing, Suite 375 • Johns Creek GA 30097

© 2023 SpillTech Environmental Corporation. All rights reserved.

SPKHZ-20 Specifications

Dimensions:	ext. dia. 23" x 19.5" H
Shipping Dimensions:	23" W x 23" L x 19" H
Sold as:	1 per package
Absorbency:	Up to 15.2 gal. per package
Weight:	22.53 lbs.
# per Pallet:	16
Incinerable:	No
Ship Class:	175
Includes:	25 - 15" x 19" Yellow HazMat HeavyWeight SonicBonded Pads (YPB100H) 4 - 3" x 4' Yellow HazMat Sorbent Socks (YSO430) 2 - 18" x 18" Yellow HazMat Sorbent Pillows (YPIL1818) 4 - 18" X 30" Yellow Disposal Bags & Ties (A-DISPBAG-SM) 1 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - 3" x 5" Vinyl Spill Kit Label (A-KITLABEL) 1 - 23" x 19" Yellow 20-Gallon OverPack (1H2/X75/S) (A20OVER) 6 - 6" x 2" TamperProof Seals (A-SEAL)

Metric Equivalent Specifications

Dimensions:	ext. dia. 58cm x 50cm H
Shipping Dimensions:	58cm W x 58cm L x 48cm H
Absorbency:	Up to 57.5 L per package
Weight:	10.2 kg

© 2023 SpillTech Environmental Corporation. All rights reserved.

SPKHZ-20 Technical Information

Warnings & Restrictions:
There are no known warnings and restrictions for this product.

Regulations and Compliance:
49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation…so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:
(Available at **spilltech.com**)

Product Data Sheet (PDS)

© 2023 SpillTech Environmental Corporation. All rights reserved.