HazMat 5-Gallon Spill Kit #SPKHZ-5 - Absorbs up to 4.6 Gallons



Be prepared for fast response with a SpillTech® HazMat Spill Kit!

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com

6455 East Johns Crossing, Suite 375 • Johns Creek GA 30097

© 2023 SpillTech Environmental Corporation. All rights reserved.

SPKHZ-5 Specifications

Dimensions:	ext. dia. 12" x 16.75" H
Shipping Dimensions:	13.4" W x 13.4" L x 17.25" H
Sold as:	1 per package
Absorbency:	Up to 4.6 gal. per package
Weight:	13.05 lbs.
# per Pallet:	24
Incinerable:	No
Ship Class:	175
Includes:	10 - 15" x 19" Yellow HazMat HeavyWeight SonicBonded Pads (YPB100H) 2 - 3" x 4' Yellow HazMat Sorbent Socks (YSO430) 2 - 18" x 30" Yellow Disposal Bag & Tie (A-DISPBAG-SM) 1 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - 3" x 5" Vinyl Spill Kit Label (A-KITLABEL) 1 - 12" x 16.75" White 5-Gallon OverPack (1H2/Y1.5/30) (A5OVER) 1 - 6" x 2" TamperProof Seals (A-SEAL)

Metric Equivalent Specifications

Dimensions:	ext. dia. 30cm x 43cm H
Shipping Dimensions:	34cm W x 34cm L x 44cm H
Absorbency:	Up to 17.4 L per package
Weight:	5.9 kg

SPKHZ-5 Technical Information

Warnings & Restrictions:
There are no known warnings and restrictions for this product.

Regulations and Compliance:
49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation…so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:
(Available at **spilltech.com**)
Product Data Sheet (PDS)

© 2023 SpillTech Environmental Corporation. All rights reserved.