95-Gallon Recycled OverPack Salvage Drum #A95OVER-RC - 32.25" dia x 41.5", 1



This eco-friendly OverPack is constructed of 100% recycled polyethylene, making it an ideal choice for a greener workplace. Stock with sorbents for emergency spill response or use it as a salvage drum to ship damaged containers or hazardous waste.

- DOT-approved and Y-rated for use as a salvage drum; conform to federal regs when shipping damaged or leaking containers of hazardous materials or absorbents contaminated with hazardous substances
- Stores sorbent products (not included) for quick response and easy access as needed for spill control
- 100% recycled polyethylene OverPack resists chemicals, rust and corrosion for years of use
- Integrated handles make it easy to lift, move or carry with standard material handling equipment
- Twist-on, double-wall lid with closed-cell gasket provides sealed, secure closure to prevent leaks and protect contents from moisture, dirt and damage
- Durable to withstand rough handling
- We can customize a Spill Kit to your exact specifications, including contents and accessories, with no upcharge! Contact your local Distributor for details.

© 2023 SpillTech Environmental Corporation. All rights reserved.

A95OVER-RC Specifications

Dimensions:	ext. dia. 32.25" x 41.5" H
Shipping Dimensions:	33" W x 33" L x 43" H
Sold as:	1 per package
Color:	Black
Composition:	Polyethylene
Recycled Content:	100% Post-Industrial Recycled Polyethylene
Weight:	48 lbs.
# per Pallet:	6
Incinerable:	No
UN RATING:	1H2/Y345/S/**/USA/M5904
Ship Class:	250

Metric Equivalent Specifications

Dimensions:	ext. dia. 81.9cm x 105.4cm H
Shipping Dimensions:	83.8cm W x 83.8cm L x 109.2cm H
Weight:	21.8 kg

A95OVER-RC Technical Information

Warnings & Restrictions:
There are no known warnings and restrictions for this product.

Regulations and Compliance:
49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

49 CFR 173.12(b)(2)(iv) - When labpacking, "Inner packagings…must be surrounded by a chemically compatible absorbent material in sufficient quantity to absorb the total liquid contents."

49 CFR 173.12(b) - A container used for labpacking must be "a UN 1A2 or UN 1B2 metal drum, a UN 1D plywood drum, a UN 1G fiber drum or a UN 1H2 plastic drum tested and marked at least for the Packing Group III performance level for liquids or solids."

Technical Documents:
(Available at **spilltech.com**)

Product Data Sheet (PDS)
Chemical Compatibility (CCG)

© 2023 SpillTech Environmental Corporation. All rights reserved.