RESCUE® Motors Permanent Split Capacitor Condenser Fan 5.6" Diameter, Totally Enclosed, Air Over (TEAO)




APPLICATIONS:

Commercial and Residential Condensing Units. Can replace a range of horsepower application and a variety of mounting styles.

FEATURES:

- High 158°F (70°C) Or 140°F (60°C) Ambient Designs
- Automatic Reset Thermal Overload Protector
- Designed For Use With 370V Capacitors
- Special Treated Rotor For Corrosion Protection
- Includes Lead End Mounting Holes For RHEEM®† or TRANE®† Units
- 48" Leads
- Extended Mounting Studs
- Ball Bearings
- Reversible Rotation
- High Efficiency Design
- Continuous Duty, Air Over
- Reversible Rotation



RESCUE® Condenser Motors available in 158°F (70°C) ambient ratings! See below

HP	RPM	Voltage	Catalog Number	List	Max. Ambient	Speed Tap	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Ship Wt.	Notes
1/3	825	208-230	5464	$182	140°F(60°C)	High	7.5	1.9	5	5.3	10.3	18	H43
1/4						High	7.5	1.5					
1/5						Low	7.5	1.2					
1/6						Low	7.5	1.0					
1/3	825	208-230	5464H	$186	158°F(70°C)	High	7.5	1.9	5	5.3	10.3	18	H43
1/4						High	7.5	1.5					
1/5						Low	7.5	1.2					
1/6						Low	7.5	1.0					
1/3	1075	208-230	5472	$160	140°F(60°C)	High	7.5	2.4	5	3.8	8.8	11	H43
1/4						High	7.5	2.4					
1/5						High	7.5	2.4					
1/6						High	7.5	2.4					
1/3	1075	208-230	5462	$140	140°F(60°C)	High	5	2.6	5	4.6	9.6	14	H43
1/4						High	5	2.5					
1/5						Low	5	2.0					
1/6						Low	5	1.8					
1/3	1075	208-230	5462H	$153	158°F(70°C)	High	5	2.6	5	4.6	9.6	14	H43
1/4						High	5	2.5					
1/5						Low	5	2.0					
1/6						Low	5	1.8					
1/2	1075	208-230	5465	$177	140°F(60°C)	High	10	3.0	5	5.3	10.3	15	H43
1/3						High	10	2.2					
1/4						Low	10	1.6					
1/5						Low	10	1.3					
1/2	1075	208-230	5465H	$190	158°F(70°C)	High	10	3	5	5.3	10.3	19	H43
1/3						High	10	2.2					
1/4						Low	10	1.6					
1/5						Low	10	1.3					
3/4	1075	208-230	5482H	$205	158°F(70°C)	High	15	4	5.5	6.3	11.8	21	H43
1/2						High	15	2.8					
1/3						Low	15	1.9					
1/4						Low	15	1.4					

460 Volt RESCUE® Condenser Fan Motors

HP	RPM	Voltage	Catalog Number	List	Max. Ambient	Speed Tap	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Ship Wt.	Notes
1/2	1075	460	5480H	$240	158°F(70°C)	High	10	1.3	5.5	5.6	11.1	20	H43
1/3						High	10	0.9					
1/4						Low	10	0.7					
1/5						Low	10	0.5					
1/6						Low	10	0.5					
3/4	1075	460	5481H	$260	158°F(70°C)	High	15	2.2	5.5	6.3	11.8	25	H43
1/2						High	15	1.3					
1/3						Low	15	1.1					
1/4						Low	15	0.7					

Note H43: Side Shell & Lead End Mounting Screws Included In Carton