ALEDL3TSFN/480/7PR



Color: Bronze

Weight: 31.5 lbs

Project:	**Type:**
Prepared By:	**Date:**

Driver Info

Type	Constant Current
120V	N/A
208V	N/A
240V	N/A
277V	N/A
Input Watts	171.5/227.5/264W

LED Info

Watts	260W
Color Temp	4000K (Neutral)
Color Accuracy	84/84/82 CRI
L70 Lifespan	100,000 Hours
Lumens	26421/34222/38288 lm
Efficacy	154.1/150.4/145 lm/W

Technical Specifications

Field Adjustability

Field Adjustable (Wattage):
Field adjustable light output in 3 discrete steps: Large Housing: 260W/220W/170W (factory default 260W)

Compliance

UL Listed:
Suitable for wet locations

IP Rating:
Ingress protection rating of IP66 for dust and water

IESNA LM-79 & LM-80 Testing:
RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

DLC Listed:
This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.
DLC Product Code: S-5CS2WG

LED Characteristics

LEDs:
Long-life, high-efficacy, discrete, surface-mount LEDs

Color Consistency:
7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Color Stability:
LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

Color Uniformity:
RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for (SSL) Products, ANSI C78.377-2017.

Electrical

Driver:
170W: Constant Current, Non-Class 2, 480V, 50/60 Hz, 480V: 0.39A

220W: Constant Current, Non-Class 2, 480V, 50/60 Hz, 480V: 0.50A

260W: Constant Current, Non-Class 2, 480V, 50/60 Hz, 480V: 0.57A

Dimming Driver:
Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

THD:
4.36% 480V

Power Factor:
96.4% at 480V

Surge Protection:
Line to Line: 10kV
Line to Ground: 6kV

7-Pin Receptacle:
ANSI C136.41 7-pin receptacle, compatible with wireless control systems

Performance

Lifespan:
100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Wattage Equivalency:
Equivalent to 1,000W Metal Halide

Construction

IES Classification:
The Type III distribution is meant to be located near the side of an area, projecting the light outward to fill the area. Ideal for roadways, general parking areas, lighting applications and where a large pool of light is required.

Cold Weather Starting:
The minimum starting temperature is -40°C (-40°F)

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Technical Specifications (continued)

Ambient Temperature :
Max Power Temp Rating: 40°C (104°F)
Middle Power Temp Rating: 43°C (110°F)
Low Power Temp Rating: 51°C (125°F)

Housing:
Die-cast aluminum

Mounting:
2 3/8" slipfitter mount with stainless steel hardware

Tilt Increment:
Rotates in 5 degree increments

Lens:
Polycarbonate lens

Reflector:
Aluminum reflector with white polycarbonate

Vibration Rating:
3G vibration rating per ANSI C136.31

Effective Projected Area:
1 Fixture: 0.65
2 Fixtures at 90°: 1.02
2 Fixtures at 180°: 1.31
3 Fixtures at 90°: 1.68
4 Fixtures at 90°: 1.68

Gaskets:
High-temperature silicone gaskets

Finish:
Formulated for high durability and long-lasting color

Green Technology:
Mercury and UV free. RoHS-compliant components.

Optical

Bug Rating:
260W: B3 U0 G4
220W: B3 U0 G4
170W: B3 U0 G4

Other

Warranty:
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of ten (10) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:
RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

ALEDL3TSFN/480/7PR

Dimensions



Features

- 0-10V dimmable standard
- IP66 Rated
- 100,000-Hour LED lifespan
- 10-Year, No-Compromise Warranty

Ordering Matrix

Family	Housing Size	Distribution	Mounting	Color Temp	Finish	Voltage	Options
ALED	L	3T	SF	N		/480	/7PR
	M = Medium (150W/90W/78W) **L =** Large (260W/220W/170W) **XL =** Extra Large (385W/345W/300W) **S =** Small (80W/60W/40W)	**2T =** Type II **3T =** Type III **4T =** Type IV **5T =** Type V **AT =** Auto Dealership Optic	**Blank =** Universal Pole Mount **SF =** Slipfitter **WM =** Wall Mount	**Blank =** 5000K Cool **Y =** 3000K Warm [1] **N =** 4000K Neutral	**Blank =** Bronze **W =** White **B =** Black	**Blank =** 120-277V, 0-10V Dimming **/480 =** 480V, 0-10V Dimming [2]	**Blank =** No Option **/7PR =** 7 Pin Twistlock Receptacle **/WS2 =** Wattstopper, 20ft lens **/WS4 =** Wattstopper, 40ft lens [3]

[1] *Dark sky approved in 3000K, available only on Small and Medium fixtures*
[2] *480V available only on Medium, Large & Extra Large fixtures*
[3] *Wattstopper option available only 0n Large & Extra Large fixtures*

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice