# ALEDS5TWMN/7PR



Color: Bronze

Weight: 13.2 lbs

| | |
|---|---|
| **Project:** | **Type:** |
| **Prepared By:** | **Date:** |

### Driver Info

| | |
|---|---|
| Type | Constant Current |
| 120V | 0.67A |
| 208V | 0.40A |
| 240V | 0.34A |
| 277V | 0.30A |
| Input Watts | 42.1/59.8/84.4W |

### LED Info

| | |
|---|---|
| Watts | 80W |
| Color Temp | 4000K (Neutral) |
| Color Accuracy | 82 CRI |
| L70 Lifespan | 100,000 Hours |
| Lumens | 6353/8746/11760 lm |
| Efficacy | 150.9/146.3/139.3 lm/W |

## Technical Specifications

### Field Adjustability

**Field Adjustable (Wattage):**
Field adjustable light output in 3 discrete steps:
Small Housing: 80W/60W/40W (factory default 80W)

### Compliance

**UL Listed:**
Suitable for wet locations

**IP Rating:**
Ingress protection rating of IP66 for dust and water

**IESNA LM-79 & LM-80 Testing:**
RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

**DLC Listed:**
This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.
DLC Product Code: S-K4QV28

### LED Characteristics

**LEDs:**
Long-life, high-efficacy, discrete, surface-mount LEDs

**Color Consistency:**
7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

**Color Stability:**
LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

**Color Uniformity:**
RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for (SSL) Products, ANSI C78.377-2017.

### Electrical

**Driver:**
40W: Constant Current, Class 2, 120-277V, 50/60 Hz, 120V: 0.34A, 208V: 0.20A, 240V: 0.17A, 277V: 0.15A

60W: Constant Current, Class 2, 120-277V, 50/60 Hz, 120V: 0.50A, 208V: 0.30A, 240V: 0.25A, 277V: 0.22A

80W: Constant Current, Class 2, 120-277V, 50/60 Hz, 120V: 0.67A, 208V: 0.40A, 240V: 0.34A, 277V: 0.30A

**Dimming Driver:**
Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

**THD:**
2.01% at 120V, 6.71% at 277V

**Power Factor:**
99.9% at 120V, 96.8% at 277V

**Surge Protection:**
Line to Line: 10kV
Line to Ground: 6kV

**7-Pin Receptacle:**
ANSI C136.41 7-pin receptacle, compatible with wireless control systems

### Performance

**Lifespan:**
100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

**Wattage Equivalency:**
Equivalent to 250W Metal Halide

### Construction

**IES Classification:**
The Type V distribution produces light in a wide and uniform 360° pattern that is perfect for large outdoor areas such as parking lots, corporate parks and retail settings


Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

## Technical Specifications (continued)

**Cold Weather Starting:**
The minimum starting temperature is -40°C (-40°F)

**Ambient Temperature :**
Max Power Temp Rating: 40°C (104°F)
Middle Power Temp Rating: 52°C (125°F)
Low Power Temp Rating: 58°C (137°F)

**Housing:**
Die-cast aluminum

**Reflector:**
Aluminum reflector with white polycarbonate

**Vibration Rating:**
3G vibration rating per ANSI C136.31

**Effective Projected Area:**
1 Fixture: 0.35
2 Fixtures at 90°: 0.54
2 Fixtures at 180°: 0.7
3 Fixtures at 90°: 0.9
4 Fixtures at 90°: 0.9

**Gaskets:**
High-temperature silicone gaskets

**Finish:**
Formulated for high durability and long-lasting color

**Green Technology:**
Mercury and UV free. RoHS-compliant components.

### Installation

**Mounting:**
Wall mount

### Optical

**Bug Rating:**
80W: B3-U0-G2
60W: B3 U0 G1
40W: B3 U0 G1

### Other

**Buy American Act Compliance:**
RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.


Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

# ALEDS5TWMN/7PR

## Dimensions




## Features

- 0-10V dimmable standard
- IP66 Rated
- 100,000-Hour LED lifespan
- 10-Year, No-Compromise Warranty

## Ordering Matrix

| Family | Housing Size | Distribution | Mounting | Color Temp | Finish | Voltage | Options |
|---|---|---|---|---|---|---|---|
| ALED | S | 5T | WM | N | | | /7PR |
| | **M =** Medium (150W/90W/78W)<br>**L =** Large (260W/220W/170W)<br>**XL =** Extra Large (385W/345W/300W)<br>**S =** Small (80W/60W/40W) | **2T =** Type II<br>**3T =** Type III<br>**4T =** Type IV<br>**5T =** Type V<br>**AT =** Auto Dealership Optic | **Blank =** Universal Pole Mount<br>**SF =** Slipfitter<br>**WM =** Wall Mount | **Blank =** 5000K Cool<br>**Y =** 3000K Warm [1]<br>**N =** 4000K Neutral | **Blank =** Bronze<br>**W =** White<br>**B =** Black | **Blank =** 120-277V, 0-10V Dimming<br>**/480 =** 480V, 0-10V Dimming [2] | **Blank =** No Option<br>**/7PR =** 7 Pin Twistlock Receptacle<br>**/WS2 =** Wattstopper, 20ft lens<br>**/WS4 =** Wattstopper, 40ft lens [3] |

[1] *Dark sky approved in 3000K, available only on Small and Medium fixtures*
[2] *480V available only on Medium, Large & Extra Large fixtures*
[3] *Wattstopper option available only 0n Large & Extra Large fixtures*


Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice