# ALEDXL2TWMNW




| | |
|---|---|
| **Project:** | **Type:** |
| **Prepared By:** | **Date:** |

### Driver Info

| | |
|---|---|
| Type | Constant Current |
| 120V | 3.21A |
| 208V | 1.85A |
| 240V | 1.60A |
| 277V | 1.39A |
| Input Watts | 292.2/316.9/371.7W |

### LED Info

| | |
|---|---|
| Watts | 385W |
| Color Temp | 4000K (Neutral) |
| Color Accuracy | 83 CRI |
| L70 Lifespan | 100,000 Hours |
| Lumens | 39482/48439/48439 lm |
| Efficacy | 135.1/133.5/130.3 lm/W |

## Technical Specifications

### Field Adjustability

**Field Adjustable (Wattage):**
Field adjustable light output in 3 discrete steps: Extra Large Housing: 385W/345W/300W/345W (factory default 385W)

### Compliance

**UL Listed:**
Suitable for wet locations

**IP Rating:**
Ingress protection rating of IP66 for dust and water

**IESNA LM-79 & LM-80 Testing:**
RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

**DLC Listed:**
This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.
DLC Product Code: S-IRJ9V3

### LED Characteristics

**LEDs:**
Long-life, high-efficacy, discrete, surface-mount LEDs

**Color Consistency:**
7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

**Color Stability:**
LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

**Color Uniformity:**
RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for (SSL) Products, ANSI C78.377-2017.

### Electrical

**Driver:**
300W: Constant Current, Non-Class 2, 120-277V, 50/60 Hz, 120V: 2.50A, 208V: 1.45A, 240V: 1.25A, 277V: 1.10A

345W: Constant Current, Non-Class 2, 120-277V, 50/60 Hz, 120V: 2.88A, 208V: 1.66A, 240V: 1.44A, 277V: 1.25A

385W: Constant Current, Non-Class 2, 120-277V, 50/60 Hz, 120V: 3.21A, 208V: 1.85A, 240V: 1.60A, 277V: 1.39A

**Dimming Driver:**
Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

**THD:**
3.06% at 120V, 9.47% at 277V

**Power Factor:**
99.9% at 120V, 96.7% at 277V

**Surge Protection:**
Line to Line: 10kV
Line to Ground: 6kV

### Performance

**Lifespan:**
100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

**Wattage Equivalency:**
Equivalent to 1,500W Metal Halide

### Construction

**IES Classification:**
The Type II distribution is meant for lighting large areas, located by the roadside. Typically found on wide walkways, on ramps, entrace roadways and bike paths.

**Cold Weather Starting:**
The minimum starting temperature is -40°C (-40°F)


Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

## Technical Specifications (continued)

**Ambient Temperature :**
Max Power Temp Rating: 40°C (104°F)
Middle Power Temp Rating: 43°C (110°F)
Low Power Temp Rating: 47°C (116°F)

**Housing:**
Die-cast aluminum

**Lens:**
Polycarbonate lens

**Reflector:**
Aluminum reflector with white polycarbonate

**Vibration Rating:**
3G vibration rating per ANSI C136.31

**Effective Projected Area:**
XL-EPA - Effective Projected Area-10137a 1 Fixture: 0.6
2 Fixtures at 90°: 0.96
2 Fixtures at 180°: 1.2
3 Fixtures at 90°: 1.56
4 Fixtures at 90°: 1.56

**Gaskets:**
High-temperature silicone gaskets

**Finish:**
Formulated for high durability and long-lasting color

**Green Technology:**
Mercury and UV free. RoHS-compliant components.

### Installation

**Mounting:**
Wall mount

### Optical

**Bug Rating:**
385W: B4 U0 G3
345W: B4 U0 G3
300W: B4 U0 G3

### Other

**Warranty:**
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of ten (10) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

**Buy American Act Compliance:**
RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.


Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

# ALEDXL2TWMNW

## Dimensions




## Features

- 0-10V dimmable standard
- IP66 Rated
- 100,000-Hour LED lifespan
- 10-Year, No-Compromise Warranty

## Ordering Matrix

| Family | Housing Size | Distribution | Mounting | Color Temp | Finish | Voltage | Options |
|---|---|---|---|---|---|---|---|
| ALED | XL | 2T | WM | N | W | | |
| | **M =** Medium (150W/90W/78W)<br>**L =** Large (260W/220W/170W)<br>**XL =** Extra Large (385W/345W/300W)<br>**S =** Small (80W/60W/40W) | **2T =** Type II<br>**3T =** Type III<br>**4T =** Type IV<br>**5T =** Type V<br>**AT =** Auto Dealership Optic | **Blank =** Universal Pole Mount<br>**SF =** Slipfitter<br>**WM =** Wall Mount | **Blank =** 5000K Cool<br>**Y =** 3000K Warm [1]<br>**N =** 4000K Neutral | **Blank =** Bronze<br>**W =** White<br>**B =** Black | **Blank =** 120-277V, 0-10V Dimming<br>**/480 =** 480V, 0-10V Dimming [2] | **Blank =** No Option<br>**/7PR =** 7 Pin Twistlock Receptacle<br>**/WS2 =** Wattstopper, 20ft lens<br>**/WS4 =** Wattstopper, 40ft lens [3] |

[1] *Dark sky approved in 3000K, available only on Small and Medium fixtures*
[2] *480V available only on Medium, Large & Extra Large fixtures*
[3] *Wattstopper option available only 0n Large & Extra Large fixtures*


Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice