ALEDM2TWMNB/480



Color: Black

Weight: 16.5 lbs

Project:	**Type:**
Prepared By:	**Date:**

Driver Info

Type	Constant Current
120V	N/A
208V	N/A
240V	N/A
277V	N/A
Input Watts	74/90.6/145W

LED Info

Watts	150W
Color Temp	4000K (Neutral)
Color Accuracy	84/84/83 CRI
L70 Lifespan	100,000 Hours
Lumens	10807/13144/19897 lm
Efficacy	146.1/145/137.2 lm/W

Technical Specifications

Field Adjustability

Field Adjustable (Wattage):
Field adjustable light output in 3 discrete steps: Medium Housing: 150W/90W/78W (factory default 150W)

Compliance

UL Listed:
Suitable for wet locations

IP Rating:
Ingress protection rating of IP66 for dust and water

IESNA LM-79 & LM-80 Testing:
RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

DLC Listed:
This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.
DLC Product Code: S-EO7S25

LED Characteristics

LEDs:
Long-life, high-efficacy, discrete, surface-mount LEDs

Color Consistency:
7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Color Stability:
LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

Color Uniformity:
RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for (SSL) Products, ANSI C78.377-2017.

Electrical

Driver:
78W: Constant Current, Class 2, 480V, 50/60 Hz, 480V:0.20A

90W: Constant Current, Class 2, 480V, 50/60 Hz, 480V:0.23A

150W: Constant Current, Non-Class 2, 480V, 50/60 Hz, 480V: 0.32A

Dimming Driver:
Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

THD:
6.06% 480V

Power Factor:
95.8% at 480V

Surge Protection:
Line to Line: 10kV
Line to Ground: 6kV

Performance

Lifespan:
100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Wattage Equivalency:
Equivalent to 400W Metal Halide

Construction

IES Classification:
The Type II distribution is meant for lighting large areas, located by the roadside. Typically found on wide walkways, on ramps, entrace roadways and bike paths.

Cold Weather Starting:
The minimum starting temperature is -40°C (-40°F)

Ambient Temperature :
Max Power Temp Rating: 40°C (104°F)
Middle Power Temp Rating: 52°C (125°F)
Low Power Temp Rating: 54°C (130°F)

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Technical Specifications (continued)

Housing:
Die-cast aluminum

Lens:
Polycarbonate lens

Reflector:
Aluminum reflector with white polycarbonate

Vibration Rating:
3G vibration rating per ANSI C136.31

Effective Projected Area:
1 Fixture: 0.37
2 Fixtures at 90°: 0.59
2 Fixtures at 180°: 0.74
3 Fixtures at 90°: 0.96
4 Fixtures at 90°: 0.96

Gaskets:
High-temperature silicone gaskets

Finish:
Formulated for high durability and long-lasting color

Green Technology:
Mercury and UV free. RoHS-compliant components.

Installation

Mounting:
Wall mount

Optical

Bug Rating:
150W: B3 U0 G2
90W: B3 U0 G2
78W: B3 U0 G1

Other

Warranty:
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of ten (10) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:
RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

ALEDM2TWMNB/480

Dimensions



Features

- 0-10V dimmable standard
- IP66 Rated
- 100,000-Hour LED lifespan
- 10-Year, No-Compromise Warranty

Ordering Matrix

Family	Housing Size	Distribution	Mounting	Color Temp	Finish	Voltage	Options
ALED	M	2T	WM	N	B	/480	
	M = Medium (150W/90W/78W) **L =** Large (260W/220W/170W) **XL =** Extra Large (385W/345W/300W) **S =** Small (80W/60W/40W)	**2T =** Type II **3T =** Type III **4T =** Type IV **5T =** Type V **AT =** Auto Dealership Optic	**Blank =** Universal Pole Mount **SF =** Slipfitter **WM =** Wall Mount	**Blank =** 5000K Cool **Y =** 3000K Warm [1] **N =** 4000K Neutral	**Blank =** Bronze **W =** White **B =** Black	**Blank =** 120-277V, 0-10V Dimming **/480 =** 480V, 0-10V Dimming [2]	**Blank =** No Option **/7PR =** 7 Pin Twistlock Receptacle **/WS2 =** Wattstopper, 20ft lens **/WS4 =** Wattstopper, 40ft lens [3]

[1] *Dark sky approved in 3000K, available only on Small and Medium fixtures*
[2] *480V available only on Medium, Large & Extra Large fixtures*
[3] *Wattstopper option available only 0n Large & Extra Large fixtures*

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice