ECOMBO34-RGR



Color: White

Weight: 1.5 lbs

Project:	Type:
Prepared By:	Date:

Technical Specifications

Performance

Product Type:
Exit Combo

Description:
Ultra-economy exit sign combo with 90-minute emergency battery backup unit.

Input Power:
1.6W @120V; 1.6W @277V

Lumens:
42lm

Lumens (per fixture):
84lm

Electrical

Power Factor:
0.11@120V; 0.05@277V

Input Voltage:
Dual 120/277 Voltage

Operating Frequency:
60Hz

Input Current @ 120V (mA):
120mA

Input Current @ 277V (mA):
110mA

Maximum Output Current (Amps):
0.28A

Maximum Output Wattage:
1W

Dual Voltage Circuit Operation:
No

Operating Temperature:
32°F to 104°F (0°C to 40°C)

Emergency Illumination:
90 minutes

Battery Backup:
Yes

Battery Type:
Nickel Cadmium

Battery Voltage:
3.6V

Recharge Time Required:
24-hours

Battery Operating Temperature:
32°C to 122°C (0°F to 50°F)

Storage Temperature:
68°F to 86°F (20°C to 30°C)

Storage Shelf Life:
3 years before the initial charge. 5 years after initial charge.

Self Diagnostics:
No, manual test only

Remote Test Switch:
No

Installation

Mounting Method:
Back/Top

Mounting Type:
Wall/Ceiling Mount

Maximum Mounting Height (ft.):
8 ft

Spacing Criteria for Emergency Egress :
14 ft on center assuming 7.5 ft mounting height with egress path 3 ft out

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Technical Specifications (continued)

Cold Weather Rated:
No

Construction

Shape:
Rectangle

Housing Material:
Thermoplastic

Housing Color:
White

Panel Material:
Thermoplastic

Panel Color:
White

Letter Color:
Red/Green

Number of Faces:
Universal Single/Double Face

Arrow Direction:
Field installable chevrons included

Sign Format:
Stencil

Remote Capacity:
Yes

No. of Heads:
2-Lamp Heads

Head Shape:
Round

Remote Head Power (W):
0.5W

Remote Head Lumens (lm):
42lm

Remote head Lumens (per fixture):
84lm

Remote Heads Replaceable:
Yes

Remote Power (W) Capacity:
1W

Compliance

Listings:
UL924 Listed

Environment:
Suitable for indoor use in dry and damp environments

IP Rating:
Indoor

Certification Model Number:
CEU3RGWRC

T20 Compliant:
Can be used to conform with the requirements of California Title 20

California Title 24 JA8 Compliant:
Not applicable

California Energy Commission (CEC) Status:
Lawful for Sales in California

FCC:
Complies with Part 15 of the FCC Rules

Other

Compatible Products:
EREMOTE-1
Single remote head
EREMOTEOUT-1
Single remote head, outdoor

5 Yr Limited Warranty:
The RAB 5-year, limited warranty covers light output, driver perfomance, paint finish and labor. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.
Battery is prorated.

Note:
All values are typical (tolerance +/- 10%)

Buy American Act Compliance:
RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Maximum Spacing Guidelines

Mounting Height	Path of Egress, 3′ Out		Path of Egress, 6′ Out		Application Notes
	Single Luminaire	Multiple Luminaires	Single Luminaire	Multiple Luminaires	
7.5′	10′	14′	13′	15′	Room Size: 50′ L x 8′W x 9′H *Direct calculation method used. Reflectances excluded.*
	Tilt: 20°	Tilt: 20°	Tilt: 40°	Tilt: 40°	
	Orient: 30°	Orient: 30°	Orient: 30°	Orient: 30°	

Note: Meets NFPA 101 illumination requirements of 1 FC average, 0.1 FC minimum, and 40:1 max:min.



Example of multiple luminaires lighting a 3′ path of egress.



Example of a single luminaire lighting a 3′ path of egress.

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

ECOMBO34-RGR

Dimensions



Features

- Universal faces with red/green letters
- Durable thermoplastic design
- 90 minutes of battery backup
- Compliant with California Title 20

Ordering Matrix

Family	Face	Heads	Exit Sign Letter Color	High Lumen	Remote Capable
ECOMBO34			RG		R
	Blank = Universal Faces	**Blank =** 2 Heads	**Blank =** Red **G =** Green **RG =** Red/Green Selectable	**Blank =** No High Lumen **H =** High Lumen	**Blank =** No Remote Capable **R =** Remote Capable

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice