EXIT-CH



Color: White

Weight: 4.9 lbs

Project:	Type:
Prepared By:	Date:

Technical Specifications

Performance

Product Type:
Chicago-Approved Steel Exit/Stair Sign

Description:
Chicago-approved exit sign with a universal face and red letters.

Input Wattage:
5W @120V and 277V

Electrical

Power Factor:
≥0.4

Input Voltage:
Dual 120/277 Voltage

Operating Frequency (Hz):
60Hz

Input Current @ 120V (mA):
10mA

Input Current @ 277V (mA):
50mA

Dual Voltage Circuit Operation:
No

Operating Temperature:
32°F to 122°F (0°C to 50°C)

Battery Backup:
AC Only

Battery Operating Temperature:
32°C to 122°C (0°F to 50°F)

Storage Temperature:
68°F to 86°F (20°C to 30°C)

Self Diagnostics:
No, manual test only

Remote Test Switch:
No

Installation

Mounting Method:
Top/End

Mounting Type:
Wall/Ceiling Mount

Cold Weather Rated:
No

Construction

Shape:
Rectangle

Housing Material:
Steel Sheet

Panel Material:
Glass

Panel Color:
White

Letter Color:
Red

Housing Color:
White

Number of Faces:
Universal Single/Double Face

Arrow Direction:
No Arrow

Sign Format:
Panel

Remote Capacity:
No

Compliance

Listings:
UL924 Listed, NFPA 101 (current Life Safety Code), NEC and OSHA illumination standards

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Technical Specifications (continued)

Environment:
Suitable for indoor use in dry and damp environments

IP Rating:
Indoor

Certification Model Number:
CAXTEU2RW-NA

T20 Compliant:
Can be used to conform with the requirements of California Title 20

California Title 24 JA8 Compliant:
Not applicable

California Energy Commission (CEC) Status:
Lawful for Sales in California

City Compliance:
Chicago Approved

FCC:
Complies with Part 15 of the FCC Rules

Other

Warranty:
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Note:
All values are typical (tolerance +/- 10%)

Buy American Act Compliance:
RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Dimensions



Features

- Double-face panel with red letters
- Steel housing
- Approved for use in the city of Chicago
- Compliant with California Title 20

Ordering Matrix

Family	Face	Exit Sign Letter Color	Arrows	Housing	State	Battery Backup	Remote Capable
EXIT					CH		
	1 = 1 Face **Blank =** Universal Faces	**Blank =** Red **G =** Green	**LRA =** Left Right Arrow **RA =** Right Arrow **LA =** Left Arrow **DA =** Double Arrow **Blank =** No Arrow	**Blank =** White Housing	**Blank =** Standard **CH =** Chicago **NY =** New York	**Blank =** No Battery Backup **/E =** Battery Backup	**Blank =** No Remote Capable **R =** Remote Capable

Copyright © 2024 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice