HUBBELL
Wiring Device-Kellems

Heavy Duty, Hospital Grade GFCI USB Receptacle, Fed Spec, A & C Ports, Tamper-Resistant/Weather-Resistant, 15A 125V, Brown



By Hubbell Wiring Device-Kellems
Catalog # GFUSBWR82AC

Fed Spec, Hospital Grade, 5-15R AUTOGUARD® Self-Testing, Self-Grounding GFCI USB

Features

- High Power 3.0 Amp, 5 Volt USB Output
- CLAD® Protection: Filters out harmonics and transient noise for precise ground fault detection.
- AutoGuard® Self-Test: Automatically tests GFCI function every 30 seconds for ongoing safety.
- Dual USB Ports: Stainless steel construction rated for 10,000 cycles
- Tamper-Resistant Shutters: Patented mechanism protects against foreign object insertion.
- Triple Wipe Construction for enhanced blade contact and long lasting plug retention
- Hubbell Quality: Engineered for long-term durability in residential, commercial, and institutional settings.

Application

Hospitals, Kitchens, Bathrooms, Outdoors

Specifications

Nema Rating	5-15R
Industry Standard(s)	Meets All NEC® Requirements
Environmental Conditions	Indoor Dry unless protected by additional means

Conductor

Number Of Poles	2-Pole
Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG

Current

Amperage Rating	15 A
Voltage Rating	125 V
Dielectric Strength	Withstands 1,500V minimum
Phase	Single Phase

Dimensions

Weight	0.5 lb.
Size	2.18x1.74x4.12

General

Specifications	• Base - Nylon • Face - Nylon • Ground Contacts - Brass • Mounting Screws - Stainless Steel • Mounting Strap - Brass • Power Contacts - Brass
Color	Brown
Style	• GFCI • USB
Mounting Type	Screw Mount
UPC	883778933769
Type	Tamper-Resistant, Weather Resistant
Insulation	UL Standards
Material	Thermoplastic/Composite
Series	Hospital Grade

Logistics

Pallet Quantity	1
Carton Quantity	10

Operational

Temperature Rating	-35°C to 66°C or -30°F to 150°F

Product Assets

Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved