Wireless Chargers

Description	Color	Rating	Receptacle	Catalog Number
Wireless wall mount phone charger.	White	Coil: 7.5 watt inductive, 125V AC input	—	USB1518

Combination Wireless Chargers

Description	Color	Rating	Receptacle	Catalog Number
Combination wireless wall mount phone charger, inductive coil with USB Type A&C ports, and tamper-resistant receptacle.	White	Coil: 7.5 watt inductive, USB: 5A 5V DC Input: 125V AC	15A 125V 20A 125V	USB1528AC USB2028AC

USB-C Power Delivery Charger Tamper-Resistant Duplex Receptacles

15A 125V NEMA 5-15R UL/CSA

20A 125V NEMA 5-20R UL/CSA

Description	Color	15A 125V	20A 125V
Type-C USB Power Delivery Charger Receptacle, two Type-C port configurations, one USB-C Power Delivery port with up to 55 Watt output and one USB Type-C convenience port with up to 1.5 Amp, 5 Volt USB output.	Black Brown Gray Ivory Light Almond White	USB15CPDBK USB15CPD USB15CPDGY USB15CPDI USB15CPDLA USB15CPDW	USB20CPDBK USB20CPD USB20CPDGY USB20CPDI USB20CPDLA USB20CPDW
Type A&C USB Power Delivery Charger Receptacle, one Type A and one Type-C port configurations, one USB-C Power Delivery port with up to 55 Watt output and one USB-A convenience port with up to 1.5 Amp, 5 Volt USB output.	Black Brown Gray Ivory Light Almond White	USB15ACPDBK USB15ACPD USB15ACPDGY USB15ACPDI USB15ACPDLA USB15ACPDW	USB20ACPDBK USB20ACPD USB20ACPDGY USB20ACPDI USB20ACPDLA USB20ACPDW

Note: See page Tech-10 for Tamper-Resistant description. See Section N for Hospital Grade series.

4 Port USB Charger Outlets

Description	Color	2 Type A and 2 Type-C ports	4 Type-C ports
USB Charger Outlets, 4 USB ports, 5 Amp, 5 Volt DC, Style Line® decorator.	Black Brown Gray Ivory Light Almond White	USB4ACBK USB4AC USB4ACGY USB4ACI USB4ACLA USB4ACW	USB4CBK USB4C USB4CGY USB4CI USB4CLA USB4CW

USB Charging Receptacles

Description		Color	15A 125V	20A 125V
USB charger duplex receptacle, 3.1 amp USB output, USB ports rated 10,000 cycles.	Two Type A port configurations	Ivory Light Almond White	USB15AI USB15ALA USB15AW	USB20AI USB20ALA USB20AW
	One Type A and one Type-C port configuration	Ivory Light Almond White	USB15ACI USB15ACLA USB15ACW	USB20ACI USB20ACLA USB20ACW

Switch Combo Outlets

Description	Color	Catalog Number
Switch Combo Outlet, two USB type 2.0 ports, 2.1 Amp, 5 Volt DC, Style Line® decorator.	Black Brown Gray Ivory Light Almond White	USB102BK USB102 USB102GY USB102I USB102LA USB102W

Weather Resistant USB Charger Duplex Receptacles

Description	Color	15A 125V	20A 125V
Type A&C USB Charger Receptacle, One Type A and one Type-C port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant USB ports rated 10,000 cycles; Commercial Grade.	Black Brown Gray Ivory Light Almond White	USB15AC5BKWR USB15AC5WR USB15AC5GYWR USB15AC5IWR USB15AC5LAWR USB15AC5WWR	USB20AC5BKWR USB20AC5WR USB20AC5GYWR USB20AC5IWR USB20AC5LAWR USB20AC5WWR

Note: Outdoor circuits should be GFCI protected per national and local electric codes.

NEC® is a registered trademark of the National Fire Protection Association (NFPA).


USB1518


USB1528AC


USB15CPDW


USB15ACPDW


USB15ACLA


USB102W


USB20ACPDW


USB15AC5WWR


USB4ACW

Dimensions in Inches (mm)