inREACH® Motorized Cord Reels

Features and Benefits

Hubbell's inREACH motorized cord reels provide a safer and more accessible cable management solution than ever before. With the press of a switch, users can easily access power cords from above.

- Durable, corrosion resistant cast aluminum housing and base
- UL Type 1
- Multi-Position Guide Arm can be mounted in two different positions
- Ratchet lock automatically maintains desired cord length or can be disengaged in the field for constant tension applications



Motorized Cord Reels

Description	Amps	Volts AC	Cable Length Feet (m)	Cable Type	Weight lbs (kg)	Catalog Number
White motorized reel without end effectors.	20	125	25 (7.6)	12/3 SJO	32 (14.5)	**HBLM25123**
Black motorized reel without end effectors.	20	125	25 (7.6)	12/3 SJO	32 (14.5)	**HBLM25123BLK**
White motorized reel with white cable and no end effectors.	20	125	25 (7.6)	12/3 SJO	32 (14.5)	**HBLMWC25123**
White motorized reel with (1) 20A Insulgrip plug.	20	125	25 (7.6)	12/3 SJO	33 (15.0)	**HBLM25123C20***
White motorized reel with (2) 20A tamper resistant duplex recpetacles.	20	125	25 (7.6)	12/3 SJO	34 (15.4)	**HBLM25123R220M1***
White motorized reel with (1) 20A tamper resistant duplex receptacle.	20	125	25 (7.6)	12/3 SJO	34 (15.4)	**HBLM25123GF20M1***
White motorized reel with GFCI module and (2) 20A duplex receptacles.	20	125	25 (7.6)	12/3 SJO	34 (15.4)	**HBLM25123GF220M1***
White reel with a white cord and (2) 20A duplex receptacles.	20	125	25 (7.6)	12/3 SJO	34 (15.4)	**HBLMWC25123R220M2***
Black motorized reel with (2) tamper resistant duplex recpetacles.	20	125	25 (7.6)	12/3 SJO	34 (15.4)	**HBLM25123BLKR220M1***
White motorized reel without end effectors.	20	125/250	25 (7.6)	12/4 SJO	33 (15.0)	**HBLM25124**
White motorized reel with (1) L14 20A Twist Lock® plug and (1) female L14 plug.	20	125/250	25 (7.6)	12/4 SJO	34 (15.4)	**HBLM25124C**
White motorized reel with (1) L14 20A Twist Lock® plug and (2) 20A duplex receptacles.	20	125/250	25 (7.6)	12/4 SJO	34 (15.4)	**HBLM25124SC**
White motorized reel without end effectors.	20	125	45 (13.7)	12/3 SJO	35 (15.9)	**HBLM45123**
Black motorized reel without end effectors.	20	125	45 (13.7)	12/3 SJO	35 (15.9)	**HBLM45123BLK**
White motorized reel with white cable and no end effectors.	20	125	45 (13.7)	12/3 SJO	35 (15.9)	**HBLMWC45123**
White motorized reel with (1) 20A Insulgrip® plug.	20	125	45 (13.7)	12/3 SJO	36 (16.3)	**HBLM45123C20**
White motorized reel with (2) 20A duplex receptacles.	20	125	45 (13.7)	12/3 SJO	37 (16.8)	**HBLM45123R220M1**
White motorized reel with (1) 20A tamper resistant duplex receptacle.	20	125	45 (13.7)	12/3 SJO	37 (16.8)	**HBLM45123GF20M1**
White motorized reel with GFCI module and (2) 20A duplex receptacles.	20	125	45 (13.7)	12/3 SJO	37 (16.8)	**HBLM45123GF220M1**
White reel with a white cord and (2) 20A duplex receptacles.	20	125	45 (13.7)	12/3 SJO	37 (16.8)	**HBLMWC45123R220M2**
Black motorized reel with (2) tamper resistant duplex recpetacles.	20	125	45 (13.7)	12/3 SJO	37 (16.8)	**HBLM45123BLKR220M1**
White motorized reel without end effectors.	20	125/250	45 (13.7)	12/4 SJO	37 (16.8)	**HBLM45124**
White motorized reel with (1) L14 20A Twist Lock® plug and (1) female L14 plug.	20	125/250	45 (13.7)	12/4 SJO	37 (16.8)	**HBLM45124C**
White motorized reel with (1) L14 20A Twist Lock® plug and (2) 20A duplex receptacles.	20	125/250	45 (13.7)	12/4 SJO	36 (16.3)	**HBLM45124SC**

*Note: Configured reels are supplied with HBL5366CST on the power supply cord. | *Options also available in 45 feet. Modify the length indication in the catalog number (ex. HBLM45123C20) | **For white cord, modify part number to HBLMWCxxxxx. Ex. HBLMWC25123. For black housing, add suffix "BLK". Ex. HBLM45123BLK.*

Dimensions in Inches (mm)