HUBBELL
Wiring Device-Kellems

USB Charger Receptacle, 20A 125V, Dual Type-C, White

By Hubbell Wiring Device-Kellems
Catalog # SNAP20UCW

SNAPConnect® USB Receptacle, 20A 125V, Two Type-C Ports, 3.0 Amp, 5 Volt DC, White



Features

- Two Type C Ports
- High Power 3 Amp, up to 9 Volt USB Output
- USB Ports Rated 10,000 Cycles
- Commercial Grade Receptacle

Application

Home, Office, Airport, Public Transit

Specifications

Environmental Conditions	Indoor Dry unless protected by additional means
EU RoHS Indicator	Contact Manufacturer
Nema Rating	5-20R
Industry Standard(s)	Meets All NEC® Requirements

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
Dielectric Strength	Withstands 1,500V minimum
Voltage Rating	125 V
Wattage	15 W
Phase	Single Phase

Dimensions

Depth	1.54 in
Weight	0.4 lb.
Height	4.13 in
Width	1.75 in
Size	1.9x4.3x2.2

General

Color	White
Style	Style Line Decorator
Sub Brand	SNAPConnect®
Series	SNAPConnect® Series
Specifications	• Base - Nylon • Face - Nylon • Mounting Screws - Zinc plated steel • Mounting Strap - Galvanized Steel
Mounting Type	Screw Mount
UPC	883778308789
Type	Two USB Type C Port
Insulation	Insulated per UL
Material	Thermoplastic/Composite

Logistics

Pallet Quantity	1
Carton Quantity	10

Operational

Temperature Rating	-35°C to 66°C or -30°F to 150°F

Product Assets

Catalog [English]
Catalog Page [English]
Installation Manual [English, French, Spanish]
Sales Drawing [English]

© 2026 Hubbell Incorporated. All rights reserved