Features and Benefits

Heavy Duty Commercial Tamper and Weather Resistant GFCI Receptacles

- Patented shutter design for tamper-resistant protection
- Meets NEC® requirements for TR (406.12) and WR (406.9), UV and corrosion resistance for harsh and damp applications
- Patented AUTOGUARD® self test technology
- Protects against line and load reversal, no power to the face or downstream if device is miswired









Tamper-Resistant Weather Resistant

Rating	Color	Standard	Assembled in USA	Isolated Ground	SNAPConnect®	Right Angle Pigtailed Terminal
15A 125V NEMA 5-15R UL CSA 0.5 HP	Almond	GFTWRST15AL	GFTWRST15ALU	GFTWRST15ALIG	GFTWRST15SNAPAL	Clear right angle terminal with 6 inch leads, 600V, #12 AWG THHN/THWN-2, Polycarbonate housing material.
	Black	GFTWRST15BK	GFTWRST15BKU	GFTWRST15BKIG	GFTWRST15SNAPBK	
	Brown	GFTWRST15	GFTWRST15U	GFTWRST15IG	GFTWRST15SNAP	
	Gray	GFTWRST15GY	GFTWRST15GYU	GFTWRST15GYIG	GFTWRST15SNAPGY	
	Ivory	GFTWRST15I	GFTWRST15IU	GFTWRST15IIG	GFTWRST15SNAPI	
	Light Almond	GFTWRST15LA	GFTWRST15LAU	GFTWRST15LAIG	GFTWRST15SNAPLA	
	Red	GFTWRST15R	GFTWRST15RU	GFTWRST15RIG	GFTWRST15SNAPR	Solid **SNAP1RA**
	White	GFTWRST15W	GFTWRST15WU	GFTWRST15WIG	GFTWRST15SNAPW	Stranded **SNAP2RA**
20A 125V NEMA 5-20R UL CSA 1 HP	Almond	GFTWRST20AL	GFTWRST20ALU	GFTWRST20ALIG	GFTWRST20SNAPAL	Same as above. Assembled in USA.
	Black	GFTWRST20BK	GFTWRST20BKU	GFTWRST20BKIG	GFTWRST20SNAPBK	
	Brown	GFTWRST20	GFTWRST20U	GFTWRST20IG	GFTWRST20SNAP	
	Gray	GFTWRST20GY	GFTWRST20GYU	GFTWRST20GYIG	GFTWRST20SNAPGY	Solid **SNAP1RANA**
	Ivory	GFTWRST20I	GFTWRST20IU	GFTWRST20IIG	GFTWRST20SNAPI	Stranded **SNAP2RANA**
	Light Almond	GFTWRST20LA	GFTWRST20LAU	GFTWRST20LAIG	GFTWRST20SNAPLA	
	Red	GFTWRST20R	GFTWRST20RU	GFTWRST20RIG	GFTWRST20SNAPR	
	White	GFTWRST20W	GFTWRST20WU	GFTWRST20WIG	GFTWRST20SNAPW	







Hospital Grade ● Tamper-Resistant Weather Resistant

Rating	Color	Standard	Assembled in USA	Isolated Ground	SNAPConnect®	Right Angle Pigtailed Terminal
15A 125V NEMA 5-15R UL CSA 0.5 HP	Almond	GFTWRST82AL	GFTWRST82ALU	GFTWRST82ALIG	GFTWRST82SNAPAL	Clear right angle terminal with 6 inch leads, 600V, #12 AWG THHN/THWN-2, Polycarbonate housing material.
	Black	GFTWRST82BK	GFTWRST82BKU	GFTWRST82BKIG	GFTWRST82SNAPBK	
	Brown	GFTWRST82	GFTWRST82U	GFTWRST82IG	GFTWRST82SNAP	
	Gray	GFTWRST82GY	GFTWRST82GYU	GFTWRST82GYIG	GFTWRST82SNAPGY	
	Ivory	GFTWRST82I	GFTWRST82IU	GFTWRST82IIG	GFTWRST82SNAPI	
	Light Almond	GFTWRST82LA	GFTWRST82LAU	GFTWRST82LAIG	GFTWRST82SNAPLA	
	Red	GFTWRST82R	GFTWRST82RU	GFTWRST82RIG	GFTWRST82SNAPR	Solid **SNAP1RA**
	White	GFTWRST82W	GFTWRST82WU	GFTWRST82WIG	GFTWRST82SNAPW	Stranded **SNAP2RA**
20A 125V NEMA 5-20R UL CSA 1 HP	Almond	GFTWRST83AL	GFTWRST83ALU	GFTWRST83ALIG	GFTWRST83SNAPAL	Same as above. Assembled in USA.
	Black	GFTWRST83BK	GFTWRST83BKU	GFTWRST83BKIG	GFTWRST83SNAPBK	
	Brown	GFTWRST83	GFTWRST83U	GFTWRST83IG	GFTWRST83SNAP	
	Gray	GFTWRST83GY	GFTWRST83GYU	GFTWRST83GYIG	GFTWRST83SNAPGY	Solid **SNAP1RANA**
	Ivory	GFTWRST83I	GFTWRST83IU	GFTWRST83IIG	GFTWRST83SNAPI	Stranded **SNAP2RANA**
	Light Almond	GFTWRST83LA	GFTWRST83LAU	GFTWRST83LAIG	GFTWRST83SNAPLA	
	Red	GFTWRST83R	GFTWRST83RU	GFTWRST83RIG	GFTWRST83SNAPR	
	White	GFTWRST83W	GFTWRST83WU	GFTWRST83WIG	GFTWRST83SNAPW	

Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption. All GFCI receptacles are furnished with a matching color nylon wallplate, 20 amp feed-through capability.

NEC® is a registered trademark of the National Fire Protection Association (NFPA).