Accessories for 20 and 30 Amp 3, 4 and 5 Wire Devices

Insulgrip® Plug and Connector Body Latching Kit

The Hubbell latching kit provides both improved safety and security through a double locking feature that makes unintentional disconnection virtually impossible – even under high vibration situations. The plug and connector body lock once when first connected, then again when you push the special position locking slide into place.



Insulgrip® Latching Kit

Description	For 3 Wire Devices	For 4 & 5 Wire Devices
For all 20A and 30A Twist-Lock Insulgrip plugs and connectors.	**SK2**	**SK3**



SK2

Valise®

IP55* SUITABILITY

Weatherproof, Seal-Tite®, Triple Seal Boots

Description	For 3 Wire Devices	For 4 & 5 Wire Devices
Yellow Seal-Tite® elastomer triple seal cover for use with Valise plugs when used in cord set and Valise connector bodies when used with flanged inlet.	**HBL60CM31V**	–
Yellow Seal-Tite® elastomer triple seal cover for use with Valise connector bodies.	**HBL60CM32V**	–

*Note: *When installed and used properly with plug and connector body combinations.*



HBL60CM31V



HBL6032

Insulgrip®

IP55* SUITABILITY

Weatherproof, Seal-Tite®, Triple Seal Boots

Description	For 3 Wire Devices	For 4 & 5 Wire Devices
Black elastomer boot for plugs when used in a cord set and connector bodies when used in flanged inlets.	**HBL6031**	**HBL6035**
Same as above except yellow.	**HBL60CM31**	**HBL60CM35**
Black elastomer boot for connector bodies when used in a cord set.	**HBL6032**	**HBL6036**
Same as above except yellow.	**HBL60CM32**	**HBL60CM36**

Angle Adapter

Description	For 3 Wire Devices	For 4 & 5 Wire Devices
Nylon, angle adapter for Insulgrip plugs and connector bodies, cord grip range .325"-.930" (8.3-24).	**HBL3WAA**	**HBL45WAA**



HBL3WAA

PLUGOUT® Lockout Devices

Description	For 3 Wire Devices	For 4 & 5 Wire Devices
Lockout device for attachable 20 and 30A locking plugs, straight body or angle types, with or without weatherproof covers.	**HLD**	**HLD**
Lockout device for 20 and 30A 3 wire angle plugs and watertight Safety-Shroud® Twist-Lock® plugs.	**HLD2**	**HLD2**

Note: See section Z for additional information on PLUGOUT Lockout devices.
**When installed and used properly with plug and connector body combinations.*



HLD

For quick visual identification of circuits or configurations.

Colored Cord Clamps*

Description	Color	For 3 Wire Devices	For 4 & 5 Wire Devices
For use with 20A and 30A Insulgrip® Twist-Lock® Plugs and Connectors. Cord diameter: 3 wire .350"-.930" (9-24), 4 & 5 wire .350" – 1.150" (9-29)	Blue	**HBLTL2CCBL**	**HBLTL3CCBL**
	Brown	**HBLTL2CCBR**	**HBLTL3CCBR**
	Green	**HBLTL2CCGR**	**HBLTL3CCGR**
	Orange	–	**HBLTL3CCOR**

*Note: *Clamp only. Contains no screws. Order in increments of 10. Not UL Listed or CSA Certified.*



Dimensions in Inches (mm)