COMMERCIAL GRADE SINGLE RECEPTACLES

Features:
- 125 VAC or 250 VAC
- Impact-Resistant Thermoplastic Body
- **With integral ground contacts locked into back, body, & face to prevent strap separation**
- Up to #10AWG Side Wire
- With Combination Head Screws
- Meets NEC Article 406.12 for tamper-resistant receptacles (for more information visit pg. W15)

For use with:

Wallplates	
LEXAN	Stainless Steel
OP7	OS7
For complete wallplate section, see Page E16 to E22.	

Industrial Covers	
4S Box	5S Box
4403	5503
For complete industrial cover section, see Page A14 & A19.	

Cat. No.	Description	Color (Cat. No. - Color Code) White	Color (Cat. No. - Color Code) Ivory	Std. Pkg.	Master Carton
SR15	15A, 125V Single Receptacle	SR15-W	SR15-I	10	200
SR15-TR NEW	15A, 125V Single Receptacle, **Tamper Resistant**	SR15-TR-W	SR15-TR-I	10	200
SR20	20A, 125V Single Receptacle	SR20-W	SR20-I	10	200
SR20-TR NEW	20A, 125V Single Receptacle, **Tamper Resistant**	SR20-TR-W	SR20-TR-I	10	200
SR15-250	15A, 250V Single Receptacle	SR15-250-W	SR15-250-I	10	200
SR20-250	20A, 250V Single Receptacle	SR20-250-W	SR20-250-I	10	200

NEW


5-15R
SR15
SR15-TR
Tamper Resistant

NEW


5-20R
SR20
SR20-TR
Tamper Resistant



6-15R
SR15-250



6-20R
SR20-250

INDUSTRIAL GRADE SINGLE RECEPTACLES

Features:
- 125~250 VAC
- Impact-Resistant Thermoplastic Body
- #10 to #4 AWG Back Terminals

For use with:

Wallplate
Stainless Steel
OS703
For complete wallplate section, see Page E16 to E22.

Industrial Covers	
4S Box	5S Box
4407	5507
For complete industrial cover section, see Page A14 & A19.	


Cat. No.	Description	Color (Cat. No. - Color Code) Black	Color (Cat. No. - Color Code) White	Dia.	Std. Pkg.	Master Carton
R50-3	50A, 3-Pole, **3-Wire Range Receptacle**, NEMA 10-50R	R50-3	-	2.11"	10	40
R30-3	30A, 3-Pole, **3-Wire Dryer Receptacle**, NEMA 10-30R	R30-3	-	2.11"	10	40
R50-4	50A, 3-Pole, **4-Wire Range Receptacle**, NEMA 14-50R	R50-4	R50-4-W	2.11"	10	40
R30-4	30A, 3-Pole, **4-Wire Dryer Receptacle**, NEMA 14-30R	R30-4	R30-4-W	2.11"	10	40




10-50R
R50-3-BK



10-30R
R30-3-BK



14-50R
R50-4-W



14-30R
R30-4-W

Wiring Devices

File E224780