SystemOne Flush Sub-Plates

Description	Catalog Number
Style Line® Decorator/GFCI (2) Style Line® decorator openings for power and/or datacom applications. (3) Non-Metallic (3.5) Metal	 **S1SP**
Hubbell 4 X 4 (4) 20A, 125V receptacles. (4) Keystone openings for Hubbell jacks or flush AV connectors. Power can be wired as single or two circuit with isolated ground capability. (4) Includes ⏻ stickers. Provided with 15 ft. wire leads Provided with 30 ft. wire leads	 **S1SP4X4** **S1SP4X4C** **S1SP4X415** **S1SP4X430**
Single Receptacle + Data Opening for 20 or 30A Twist-Lock® receptacle (1.56" OD) and (2) Keystone openings for Hubbell jacks or flush AV connectors. (4)	 **S1SPTL**
Hubbell DataCom + Style Line® Decorator (1) Style Line® decorator opening, (2) flush Keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications. (5)	 **S1SPSL2IM**
Extron® or FSR + Power (1) 20A, 125V receptacle. Recessed opening for (3) single Extron® MAAP series adapter plates or FSR IPS plates. (4) Marked with "⏻ Controlled"	 **S1SPEXT1** **S1SPEXT1C**
Extron® AAP + Power (1) 20A, 125V receptacle. (2) flush Keystone & recessed opening for (2) single Extron® AAP Series adapter plates. (4) Marked with "⏻ Controlled"	 **S1SPEXT4** **S1SPEXT4C**
Panduit Mini Com® 4 X 4 (4) 20A, 125V receptacles. (4) Openings for Panduit Mini-Com Connectivity. (4) Includes ⏻ stickers.	 **S1SP4X4PA** **S1SP4X4PAC**

Description	Catalog Number
Duplex/Duplex (2) Duplex openings for power and/or datacom applications. (3) Non-Metallic (3.5) Metal	 **S1SPDU**
Carpet Furniture Feed Cover/Flange* (1) ¾" and (1) 1½" NPT access holes for power and/or datacom applications. Universal Cover not required. Includes carpet flange. (3) Non-Metallic (3.5) Metal Aluminum Fin. Brass Finish Black Gray	 **S1SPFFAL** **S1SPFFBRS** **S1SPFFBL** **S1SPFFGY**
Hubbell DataCom + Power (1) 20A, 125V receptacle and 3-unit recessed Hubbell iSTATION opening for data, voice, and AV applications. (5) Marked with "⏻ Controlled"	 **S1SP3IM** **S1SP3IMC**
Hubbell DataCom 1 unit flush Hubbell iSTATION opening and 3-unit recessed Hubbell iSTATION opening for data, voice, and AV applications. (3.5)	 **S1SP4IM**
Extron® or FSR + Power (1) 20A, 125V receptacle. Recessed opening for (1) single Extron® MAAP and (2) single AAP series adapter plates or FSR IPS plates. (4) Marked with "⏻ Controlled"	 **S1SPEXT2** **S1SPEXT2C**
Ortronics Series II® + Power (1) 20A, 125V receptacle. Recessed opening for (3) 1 unit Ortronics Series II® modules. (5) Marked with "⏻ Controlled"	 **S1SPORT** **S1SPORTC**
SYSTIMAX® 4 X 4 (4) 20A, 125V receptacles. (4) Openings for SYSTIMAX® Connectivity. (4) Includes ⏻ stickers.	 **S1SP4X4SYS** **S1SP4X4SYSC**

Description	Catalog Number
Duplex/Style Line® Decorator (1) Duplex and (1) Style Line® decorator opening for power and/or datacom applications. (3) Non-Metallic (3.5) Metal	 **S1SPDUSL**
Tile Furniture Feed Cover/Flange* (1) ¾" and (1) 1½" NPT access holes for power and/or datacom applications. Universal Cover not required. Includes tile flange. (3) Non-Metallic (3.5) Metal Aluminum Fin. Brass Finish Black Gray	 **S1SPFFTAL** **S1SPFFTBRS** **S1SPFFTBL** **S1SPFFTGY**
Hubbell DataCom + Duplex (1) Duplex opening, (2) flush Keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications. (5)	 **S1SPDU2IM**
Active Multimedia + Power Single 20A, 125V receptacle; (2) flush Keystone openings; (1) rectangular Style Line® decorator opening to accommodate active multimedia modules or low voltage outlet frames. (5) Marked with "⏻ Controlled"	 **S1SPAMM20** **S1SPAMM20C**
Extron® or FSR Single-Service Recessed opening for (2) single Extron® MAAP and (2) single AAP series adapter plates or FSR IPS plates. (4.5)	 **S1SPEXT3**
Ortronics TracJack® + Power (1) 20A, 125V receptacle. Recessed bezel for (6) Ortronics TracJack® modules. (5) Marked with "⏻ Controlled"	 **S1SPTRAC** **S1SPTRACC**
Siemon MAX® + Power (1) 20A, 125V receptacle. Recessed bezel for (6) Siemon MAX® modules. (5) Marked with "⏻ Controlled"	 **S1SPMAX** **S1SPMAXC**

*Note: *Furnished with two screws in flexible metal conduit connectors.*
⏀ Signifies minimum depth of concrete pour in inches for Metal Floor Boxes (**S1CFB**, **S1SFB** and **S1SFBAV**) and Non-Metallic Floor Box (**S1PFB**).

Sub-Plate Accessories

Replacement Threaded Conduit Plugs
Used with **S1SPFFx** and **S1SPFFTx** only.
Sub-plate is supplied with plugs.



Color	1½" Plug	¾" Plug
Aluminum Finish	**S1FP15AL**	**S1FP34AL**
Brass Finish	**S1FP15BRS**	**S1FP34BRS**
Black	**S1FP15BL**	**S1FP34BL**
Gray	**S1FP15GY**	**S1FP34GY**

Description	Catalog Number	
Replacement for **S1SPMAX.** Sub-plate is supplied with data frame. Works with Siemon MAX®.	**S1DFMAX**	
Replacement for **S1SPTRAC** sub-plate. Sub-plate is supplied with data frame. Works with Ortronics TracJack®.	**S1DFTRAC**	
Blank Style Line® decorator frame, Black.	**NS620BK**	
2-Port Style Line® decorator frame, Black.	**ISF2BK**	
4-Port Style Line® decorator frame, Black.	**ISF4BK**	
6-Port Style Line® decorator frame, Black.	**ISF6BK**	

Extron® is a registered trademark of Extron Electronics. MAX® is a registered trademark of The Siemon Company. Mini-Com® and Panduit® are registered trademarks of Panduit Corp. SYSTIMAX® is a registered trademark of CommScope, Inc. TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.