
15 and 20 Ampere, 125 Volts

Meets UL Standard 943 Class A GFCI

Fed.Spec.

SNAP*Connect*® GFCI LED


Description	Color	15A 125V NEMA 5-15R UL CSA 0.5 HP	20A 125V NEMA 5-20R UL CSA 1 HP
SNAPConnect GFCI LED, self-grounding staple, requires connector below, sold separately. Add "NA" suffix for devices Assembled in USA.	Almond	**GFRST15SNAPAL**	**GFRST20SNAPAL**
	Black	**GFRST15SNAPBK**	**GFRST20SNAPBK**
	Brown	**GFRST15SNAP**	**GFRST20SNAP**
	Gray	**GFRST15SNAPGY**	**GFRST20SNAPGY**
	Ivory	**GFRST15SNAPI**	**GFRST20SNAPI**
	Light Almond	**GFRST15SNAPLA**	**GFRST20SNAPLA**
	Red	**GFRST15SNAPR**	**GFRST20SNAPR**
	White	**GFRST15SNAPW**	**GFRST20SNAPW**



GFRST15SNAPGY

SNAP*Connect*® GFCI LED, Tamper and Weather Resistant


Description	Color	15A 125V NEMA 5-15R UL CSA 0.5 HP	20A 125V NEMA 5-20R UL CSA 1 HP
SNAPConnect GFCI TR/WR, self-grounding staple, requires connector below, sold separately. Add "NA" suffix for devices Assembled in USA.	Almond	**GFTWRST15SNAPAL**	**GFTWRST20SNAPAL**
	Black	**GFTWRST15SNAPBK**	**GFTWRST20SNAPBK**
	Brown	**GFTWRST15SNAP**	**GFTWRST20SNAP**
	Gray	**GFTWRST15SNAPGY**	**GFTWRST20SNAPGY**
	Ivory	**GFTWRST15SNAPI**	**GFTWRST20SNAPI**
	Light Almond	**GFTWRST15SNAPLA**	**GFTWRST20SNAPLA**
	Red	**GFTWRST15SNAPR**	**GFTWRST20SNAPR**
	White	**GFTWRST15SNAPW**	**GFTWRST20SNAPW**



GFTWRST20SNAPI

SNAP*Connect*® USB Charger, Duplex Receptacles


Description	Color	15A 125V NEMA 5-15R UL CSA 0.5 HP	20A 125V NEMA 5-20R UL CSA 1 HP
SNAP*Connect* USB Charger, Tamper-Resistant Style Line® decorator duplex receptacle, two USB type 2.0 ports 3 Amp, 5 Volt DC, 15 or 20 Amp, 125 Volt AC.	Black	**SNAP15USBBK**	**SNAP20USBBK**
	Brown	**SNAP15USB**	**SNAP20USB**
	Gray	**SNAP15USBGY**	**SNAP20USBGY**
	Ivory	**SNAP15USBI**	**SNAP20USBI**
	Light Almond	**SNAP15USBLA**	**SNAP20USBLA**
	White	**SNAP15USBW**	**SNAP20USBW**



SNAP15USBW

SNAP*Connect*® Surge Protection, Tamper-Resistant Receptacle with Power Indicating LED


Description	Color	15A 125V NEMA 5-15R UL CSA 0.5 HP	20A 125V NEMA 5-20R UL CSA 1 HP
SNAP*Connect* Surge supression, Tamper-Resistant, smooth face, duplex receptacle.	Blue	**SNAP5262S**	**SNAP5362S**
	Gray	**SNAP5262GYS**	**SNAP5362GYS**
	Ivory	**SNAP5262IS**	**SNAP5362IS**
	Light Almond	**SNAP5262LAS**	**SNAP5362LAS**
	White	**SNAP5262WS**	**SNAP5362WS**



SNAP5262S

SNAP*Connect*® Tester

Description	Catalog Number
Circuit Tester for SNAPConnect receptacle terminals, GFCI and standard receptacles.	**SNAPCTG**



SNAPCTG

Note: See page Tech-10 for Tamper-Resistant, Weather Resistant and LED Power Indicators descriptions.

Dimensions in Inches (mm)