


15 and 20 Ampere, 125 Volts




GFRST83SNAPR




GFTWRST83SNAPI



SNAP8300USBW



SNAP8262S



SNAP1RA

Dimensions in Inches (mm)

Meets UL Standard 943 Class A GFCI

Fed.Spec.

SNAP*Connect*® GFCI LED Hospital Grade ●

15A 125V NEMA 5-15R UL CSA 0.5 HP

20A 125V NEMA 5-20R UL CSA 1 HP

Description	Color	Catalog Number	
Hospital Grade SNAPConnect GFCI LED, self-grounding staple, requires connector below, sold separately. Add "NA" suffix for devices Assembled in USA.	Almond	**GFRST82SNAPAL**	**GFRST83SNAPAL**
	Black	**GFRST82SNAPBK**	**GFRST83SNAPBK**
	Brown	**GFRST82SNAP**	**GFRST83SNAP**
	Gray	**GFRST82SNAPGY**	**GFRST83SNAPGY**
	Ivory	**GFRST82SNAPI**	**GFRST83SNAPI**
	Light Almond	**GFRST82SNAPLA**	**GFRST83SNAPLA**
	Red	**GFRST82SNAPR**	**GFRST83SNAPR**
	White	**GFRST82SNAPW**	**GFRST83SNAPW**

SNAP*Connect*® GFCI LED Hospital Grade ●, Tamper and Weather Resistant

Description	Color	Catalog Number	
Hospital Grade SNAPConnect GFCI TR/WR, self-grounding staple, requires connector below, sold separately. Add "NA" suffix for devices Assembled in USA.	Almond	**GFTWRST82SNAPAL**	**GFTWRST83SNAPAL**
	Black	**GFTWRST82SNAPBK**	**GFTWRST83SNAPBK**
	Brown	**GFTWRST82SNAP**	**GFTWRST83SNAP**
	Gray	**GFTWRST82SNAPGY**	**GFTWRST83SNAPGY**
	Ivory	**GFTWRST82SNAPI**	**GFTWRST83SNAPI**
	Light Almond	**GFTWRST82SNAPLA**	**GFTWRST83SNAPLA**
	Red	**GFTWRST82SNAPR**	**GFTWRST83SNAPR**
	White	**GFTWRST82SNAPW**	**GFTWRST83SNAPW**

SNAP*Connect*® USB Charger Hospital Grade ●, Duplex Receptacles

15A 125V NEMA 5-15R UL CSA 0.5 HP

20A 125V NEMA 5-20R UL CSA 1 HP

Description	Color	Catalog Number	
Hospital Grade SNAP*Connect* USB Charger, Tamper-Resistant Style Line® decorator duplex receptacle, two USB type 2.0 ports 3 Amp, 5 Volt DC, 15 or 20 Amp, 125 Volt AC.	Black	**SNAP8200USBBK**	**SNAP8300USBBK**
	Brown	**SNAP8200USB**	**SNAP8300USB**
	Gray	**SNAP8200USBGY**	**SNAP8300USBGY**
	Ivory	**SNAP8200USBI**	**SNAP8300USBI**
	Light Almond	**SNAP8200USBLA**	**SNAP8300USBLA**
	Red	**SNAP8200USBR**	**SNAP8300USBR**
	White	**SNAP8200USBW**	**SNAP8300USBW**

SNAP*Connect*® Surge Protection Hospital Grade ●, Tamper-Resistant Receptacle with Power Indicating LED

15A 125V NEMA 5-15R UL CSA 0.5 HP

20A 125V NEMA 5-20R UL CSA 1 HP

Description	Color	Catalog Number	
Hospital Grade SNAP*Connect* Surge supression, Tamper-Resistant, smooth face, duplex receptacle.	Blue	**SNAP8262S**	**SNAP8362S**
	Gray	**SNAP8262GYS**	**SNAP8362GYS**
	Ivory	**SNAP8262IS**	**SNAP8362IS**
	Light Almond	**SNAP8262LAS**	**SNAP8362LAS**
	Red	**SNAP8262RS**	**SNAP8362RS**
	White	**SNAP8262WS**	**SNAP8362WS**

SNAP*Connect*® Right Angle Pigtailed Terminal

Description	Wire Type	General Use Catalog Number	Assembled in USA Catalog Number
Clear right angle terminal with 6 inch leads #12 AWG THHN/THWN-2; Polycarbonate housing material.	Solid	**SNAP1RA**	**SNAP1RNA**
	Stranded	**SNAP2RA**	**SNAP2RNA**

Note: See page Tech-10 for Tamper-Resistant, Weather Resistant and LED Power Indicators descriptions.