

Duty: Light

Rolling Elements: Ball

Housing: Stamped Steel Rubber Mounted Flange

Lock: Setscrew

Seal: Felt

Optional Seal: Contact

Temperature: -20° to 220°F

Relube: No





SRF Series Light Duty Rubber Mounted Flange Blocks - Setscrew Locking

Bore Diameter inch	Part No.	Bearing Insert No.	Max. Steady Radial Loads lb/N	Dimensions inch / mm									Bolt Size	Unit Wt. lb/kg
				A	B	D	H	J	K	M	T	Hole Size		
1/2	SRF-8	SRC-8	400 1779	4 1/2 114.3	3 5/8 92.1	1 3/32 27.8	1 3/8 34.9	1 9/32 32.5	7/8 22.2	2 41/64 67.1	2 45/64 68.7	7/16 11.1	3/8	.75 .34
5/8	SRF-10	SRC-10												
3/4	SRF-12	SRC-12												
7/8	SRF-14	SRC-14	400 1779	4 1/2 114.3	3 5/8 92.1	1 3/32 27.8	1 3/8 34.9	1 3/8 34.9	7/8 22.2	2 41/64 67.1	2 45/64 68.7	7/16 11.1	3/8	.85 .39
15/16	SRF-15	SRC-15												
1	SRF-16	SRC-16												
1 1/8	SRF-18	SRC-18	600 2669	5 3/8 136.5	4 3/8 111.1	1 1/4 31.8	1 21/32 42.1	1 5/8 41.3	1 1/16 27.0	3 1/4 82.6	3 1/2 88.9	1/2 12.7	7/16	1.50 .68
1 3/16	SRF-19	SRC-19												
1 1/4	SRF-20R	SRC-20R												

Maximum steady radial load is based upon the housing strength and materials composition. Thrust load ratings 40% of radial loads..